




76 200
LUMENS



220 800
LUMENS



LUMAPHORE® LED Dimmable 600 XLG - 1500 XLG

New



Advantages :

- Large and uniform lighting area
- Robust
- Compact
- Easy to deploy, store and transport
- Low Power Consumption
- Dimmable 1 to 100%
- Operate on main supply and on generator
- Light efficiency 150 Lm/watt
- LED technology : long life
- Immediate relighting



LUMAPHORE[®] LED 600XLG / 1500XLG

Electrical Specifications	600XLG	1500XLG
Total Lighting Output	520W	1500 W
Power of electricity supply	635 W	1720 W

Safety Specifications	600XLG	1500XLG
Protection index	IP65 / IK10	IP54 / IK08
Wind resistance	162 Km/h	110 Km/h
Thermal protection	Yes	
Temperature range for use	-15°/+40°	

Photometric Specifications	600XLG	1500XLG
Area of illumination	3200 m ²	6000 m ²
Colour temperature	5000 °K	
total Lumens	76200 lm	220 800 lm
Color rendering index	> 80	

Mechanical Specifications	600XLG	1500XLG
Diameter	22,5 cm	40 cm
Length	91 cm	93 cm
Weight	8,7 Kg	17 Kg
Spigot type	Diameter 26 mm	
Optimal height for use	4 m	5 to 7 m
Average assembly time	2 mn	

Standard package	600XLG	1500XLG
Standard Flight-case	✓	✓
power cable (Schuko plug)	9,4M	11,4m
Ring of Suspension	✓	✗
IP65 Switch (ON/OFF - Gradation)	✓	✓
Spigot (diam. 26mm)	✓	✓
Dimming 1%-100%	✓	✓

Options & Accessories	600XLG	1500XL
additional power cable length	Option	Option
Special plug (Marechal, IP67, IP68, ...)	Option	Option
Flight-case IP67	Option	✗
Spigot (diam. , DIN, ...)	When ordering	When ordering

