

DF 110000



| TECHNICAL SPECIFICATIONS | DF 110000 |
|---|--------------------------|
| Electrical engine power (fan) | 108 kW |
| Coverage (without wind) | 110 - 120 m |
| Water connection | UNI 45 / STORZ / CAMLOCK |
| Minimum inlet pressure | 1,0 bar |
| Water consumption | 150 - 315 L/min |
| Water inlet filter | 180 µm |
| Working angle | 320° |
| Tilting | 0 - 40° |
| Dimensions without electrical cabinet (L x W x H) | 2500 x 2200 x 2470 mm |
| Dimensions of electrical cabinet (L x W x H) | 1300 x 700 x 2150 mm |
| Weight (without electrical cabinet) | 2900 kg |
| Weight of electrical cabinet | 475 kg |

Values may vary depending on requested tensions and frequencies.

STANDARD EQUIPMENT

- Control panel on separated electrical cabinet
- Integrated multistage water pump
- Flowmeter for pump protection
- Pressure gauge for outlet pressure reading
- Double stainless steel crown with nozzles
- Water drain system
- Mounted on base with forklift pockets
- Electric tilting
- Automatic rotation system
- Remote control to switch on/off the fan, the pump and the electrical rotation, complete with macro-sequential controls

OPTIONAL

- Dosing pump for chemical additives
- 2,2 kW water supply pump

