

DF MINI DUO ASB

IDEAL FOR ASBESTOS REMOVAL



STANDARD EQUIPMENT

- Stainless steel 70 L water tank
- 3 interchangeable type of nozzles for different coverages
- Wheels and handles for transport
- High pressure pump
- Signal for low water level
- Adjustable satellites for an easy transport
- Manually adjustable nozzles spray angle

OPTIONAL

- Connection from the Water Supply network
- Dedicated colour (RAL)
- 110V Kit
- Plastic box for documents

TECHNICAL SPECIFICATIONS	DF MINI DUO ASB
Pump	230 V - 50 Hz - 2,6 A - 0,55 Kw - 100 bar
Nozzles spray angle	From 80° to 150°
Tilting head (high - low)	25° - 15°
3 different nozzles available	Type 1: Distance: 8+8 m - Running time 40 min - Coverage: 83+83 m ² Type 2 (std.): Distance: 7+7 m - Running time 1 h 12 min - Coverage: 64+64 m ² Type 3: Distance: 5+5 m - Running time 2 h 40 min - Coverage: 33+33 m ²
Water tank capacity	70 L
Main unit dimensions (L x W x H)	710 x 600 x 1030 mm
Satellite dimensions (L x W x H)	620 X 370 X 1800 mm
Main unit dry weight	61 kg
Satellite weight (each)	21,5 kg