



GX200

196 CM³ / 4,1 KW

3600 RPM/MIN

H 500 C

TIPO MOTORE

4 TEMPI OHV

ENGINE TYPE

**4 STROKES,
SINGLE CYLINDER OHV**

SISTEMA AVVIAMENTO

**MANUALE
O ELETTRICO**

(in optional)

STARTING SYSTEM

**MANUAL
OR ELECTRIC**

(in optional)

CAPACITA' DI CARICO
(PIANO/PENDENZA)

500 KG / 350 KG

MAX PAYLOAD

(FLAT/SLOPE)

500 KG / 350 KG

PENDENZA SUPERABILE

20%

MAX GREADABILITY

20%

PESO NETTO

395 KG

NET WEIGHT

395 KG

DIMENSIONI INGOMBRO

147,8x83,5x125 CM

OVERALL DIMENSIONS

147,8x83,5x125 CM

DIMENSIONI CASSONE

105x72x51 CM

TIPPER DIMENSIONS

105x72x51 CM

SISTEMA DI RIBALTAMENTO

**IDRAULICO
PRESSIONE 160BAR
PORTATA 12,6 LT/M
CILINDRO IDRAULICO
DOPPIO EFFETTO**

TIPPING SYSTEM

**HYDRAULIC
PRESSURE - 160 BAR
MAX PUMPFLOW - 12,6 L/MIN
DOUBLE EFFECT
HYDRAULIC CYLINDER**

TAGLIA CINGOLI

180x60x38

RUBBER TRACK SIZE

180x60x38