



GX200
196 CM3 / 4,1 KW
3600 RPM/MIN

M 500 H

TIPO MOTORE
4 TEMPI OHV

ENGINE TYPE
**4 STROKES,
MONOCYLINDER OHV**

TRASMISSIONE
6 AV / 2 RE

GEARBOX
6 FW / 2 BW

SISTEMA AVVIAMENTO
**MANUALE
O ELETTRICO**
(in optional)

STARTING SYSTEM
**MANUAL
OR ELECTRIC**
(in optional)

CAPACITA' DI CARICO
(PIANO/PENDENZA)
500 KG / 350 KG

MAX PAYLOAD
(FLAT/SLOPE)
500 KG / 350 KG

PENDENZA SUPERABILE
35%

MAX GREADABILITY
35%

PESO NETTO
195 KG

NET WEIGHT
195 KG

DIMENSIONI INGOMBRO
196x63x99 CM

OVERALL DIMENSIONS
196x63x99 CM

DIMENSIONI CASSONE
109x54x31,4 CM

TIPPER DIMENSIONS
109x54x31,4 CM

SISTEMA DI RIBALTAMENTO
IDRAULICO
PRESSIONE 160BAR
PORTATA 9,6 LT/M
CILINDRO IDRAULICO
DOPPIO EFFETTO

TIPPING SYSTEM
HYDRAULIC
PRESSURE - 160 BAR
MAX PUMFLOW - 9,6 L/MIN
DOUBLE EFFECT
HYDRAULIC CYLINDER

TAGLIA CINGOLI
180x60x42

RUBBER TRACK SIZE
180x60x42