

EMI 3000IE

Generatore inverter silenzioso
Soundproof inverter generators
Générateurs inverter insonorisés



CARATTERISTICHE: SPECIFICATIONS: CARACTÉRISTIQUES:

Motore Stage V - 4 tempi Engine Stage v - 4stroke Moteur Stage V - 4 temps	R210I
Raffreddato ad aria Air cooled Refroidi par air	Yes
Cilindrata Displacement Déplacement	212 cc
Sistema di avviamento Starting system Système de démarrage	A strappo - Elettrico Recoil - Electric
Frequenza nominale Rated frequency Fréquence nominale	50 Hz
Tensione nominale Rated voltage Tension nominale	230 V
Potenza nominale Rated power Puissance nominale	3.0 Kw
Potenza massima Max power Puissance maximum	3.3 Kw

Carburante Fuel Carburant	Benzina Gasoline Essence
Uscita DC Dc output Sortie DC	12 V/8.3 A
Capacità serbatoio Fuel tank capacity Capacité du réservoir de carburant	10 L
Autonomia a pieno carico Full load continuous running time Fonctionnement continu à pleine charge	5 h
Rumore (7 m) Noise (7m) Bruit (7 mètres)	69 dB
Dimensioni Dimensions Dimensions	645x480x500 mm
Peso Weight Poids	46 Kg
Carrello Trolley Trolley	Incluso Included
Prese Socket Price	2 x shuko16 A