



UV	UV-EXTREME NEW	UV-EXTREME PLUS NEW
Product number	03.5272	03.5273
Light source	UV LED	UV LED
Irradiance	<p>At 60 cm distance Curing diameter: ø 95 cm Min. irradiance: >6 mW/cm² Center irradiance: 16 mW/cm²</p> <p>At 40 cm distance Curing diameter: ø 90 cm Min. irradiance: >6 mW/cm² Center irradiance: 35 mW/cm²</p> <p>At 10 cm distance Curing diameter: ø 22 cm Min. irradiance: >80 mW/cm² Center irradiance: 398 mW/cm²</p>	<p>At 80 cm distance Curing size: 135x130 cm Min. irradiance: >6 mW/cm² Center irradiance: 18 mW/cm²</p> <p>At 40 cm distance Curing size: 110x100 cm Min. irradiance: >6 mW/cm² Center irradiance: 68 mW/cm²</p> <p>At 10 cm distance Curing size: 34x24 cm Min. irradiance: >120mW/cm² Center irradiance: 490mW/cm²</p>
Curing area	<p>7000 cm² at 60 cm distance 6300 cm² at 40 cm distance 380 cm² at 10 cm distance</p>	<p>13000cm² at 80 cm distance 8500cm² at 40 cm distance 640cm² at 10 cm distance</p>
Wavelength	395-400nm	395-400nm
Protection class	IP30	IP30
Impact protection	IK08	IK08
Impact resistance	1 m	1 m
Cable	5 m / 2x1.0 mm ² H05RN-F	5 m / 2x1.0 mm ² H05RN-F
Operating voltage AC	220-240 V	220-240 V
Charging voltage/current DC	-	-
Power consumption	300 W	600 W
Temperature	-10° to +40°C	-10° to +40°C
Dimensions	278 x 241 x 160 mm	415 x 241 x 160 mm
Net weight	4.95 kg	6.70 kg