

MARINER MARINER

910 B 960 B

8.6 kW 50 Hz 9.6 kW 60 Hz



CBU control panel (Mod-Bus transmission Unit)

New design, latest technology, big display and soft touch buttons for quick menu navigation, start and stop procedure, IP54 protection grade. Very compact 86x124mm (3.84x4.9 in) with a shielded connecting cable 10mts (32.8 ft) long, CBU has many functions for an easy monitoring of the generator:

- ON/OFF/START/STOP/MENU controls.
- Digital hour-meter, Main voltage, Generator Battery voltage, external battery pack voltage, Frequency, Service time, Event list of last 10 alarms and time.
- 13 different alarms icons displayed.
- 485 Mod-Bus connector for monitoring generator by boat main control monitor.

Engine

- Easy access in case of maintenance of feeding system, lubrication system, sea/water pump and air filter.
- Safety stop in case of low oil pressure.
- Safety stop in case high engine temperature or exhaust gas temperature.
- Oil filter and fuel filter easy to replace.

Alternator

- Synchronous, 2 poles, self-regulated, brush less self-excited.
- Rotor and stator epoxy resin coated against external agents.
- Rotor dynamically balanced.
- Insulation class H.
- Safety stop for high coilings temperature.

Soundproof cabin

A new design cabin composed by aluminum painted panels 5754 type, that has a very high resistance to external agents.

Thanks to this structure, soundproof cabin has a very limited weight and an easy accessibility for maintenance services, also if installed in narrow places.

Engine	50 Hz	60Hz
Model	KUBOTA D722	
Type	Diesel 4 stroke	
Cylinders (nr.)	3	
Cylinder block material	Cast iron	
Bore (mm. - in.)	67 - 2,6	
Stroke (mm.- in.)	68 - 2,6	
Displacement (cc. - CID)	722 - 43.88	
Power (hp)	16,6	20
RPM	3000	3600
Injection system	Indirect	
Engine head material	Cast iron	
Speed governor	Centrifugal mechanical	
Lubrication system	Forced	
Engine stop system	Stop solenoid	
Fuel pump	Electric	
Fuel pump discharge (cm-ft)	70 - 2,3	
Starting battery (Ah-V)	45 - 12	
Starter (kW-V)	0,7 - 12	
Max. inclination	30°	
Water pump flow (l/min. - g/min.)	20 - 5,3	

Alternator	50 Hz	60Hz
Type	Synchronous, 4-poles self excited	
Cooling	Air	
Voltage (V)	115 - 230	120 - 240
Frequency (Hz)	50	60
Amps	74,8 - 37,4	84 - 42
Max. power (kW)	8,6	9,6
Continuous power (kW)	7,8	8,8
Power factor (cos ϕ)	1	
Insulating class	H	
Voltage stability	±10%	
Frequency stability	±5%	

Cooling system

The cooling system of the engine is based on a intercooler system heat exchanger (sea water/air) with the main function of reducing the temperature of the air flow inside the soundproof cabin. The system provides an efficient cooling of the alternator and the optimal temperature for the best performance and reliability of the gensets; despite the on board allocation and the room temperature.

	50 Hz	60Hz
Dimension (Lenght x Width x Height.)	728 x 527 x 549 mm - 28,7x20,7x21,6 (in.)	
Weight	135 Kg. - 297 (lb)	

FITTINGS

- EXHAUST COMPONENTS KIT
- SIPHON BREAK
- WATER-GAS SEPARATOR KIT
- STARTING REMOTE CONTROL PANEL WITH INSTRUMENTS

*This drawing is only a reference and is not indicated for the installation. For more information, you may contact your local dealer or **mase** generators S.p.A..*

***mase** generators S.p.A. reserves the right to change the design or specifications without notice and without any obligations or liability whatsoever. For more information, you may contact your local **mase** dealer.*

Dealer:



MASE GENERATORS S.p.A. Via Tortona, 345
47522 Cesena (FC) Italy
Tel.+39-0547-354311 Fax.+39-0547-317555
Email : mase@masegenerators.com