

EA 80 GH

PORTABLE SINGLE-PHASE POWER GENERATOR /
OUTPUT POWER **7 KVA** SINGLE-PHASE /
PETROL ENGINE **3000 RPM**

Gen Set Features	<ul style="list-style-type: none">+ Low oil level cut out device+ 1 x 32A, 230 V - 50 Hz single-phase EEC socket protected by circuit breaker+ 1 x 16A, 230 V - 50 Hz single-phase EEC socket protected by circuit breaker+ 1 x 12V DC battery charger outlet protected by fuse+ Earth Leakage Circuit Breaker (ELCB)
Gen Set Options (available as factory options)	<ul style="list-style-type: none">+ Not available
Accessories on Request	<ul style="list-style-type: none">+ Trolley: two-wheels and handles
Noise Level	<ul style="list-style-type: none">+ LWA 97 (72 dB at 7m)
AC Generator 50 Hz	<ul style="list-style-type: none">+ Type synchronous+ Single-phase power (max.) 7 kVA - 230 V+ Battery Charger 120 W - 12 V - 10 A - CC+ Power Factor 0,8
Petrol Engine 3000 rpm	<ul style="list-style-type: none">+ Type Honda GX 390 OHV - 1 cyl. - 13 HP (9,6 kWm) - 390 cm³+ Fuel petrol+ Cooling system air+ Starting system manual recoil+ Fuel tank capacity 6,5 l+ Fuel consumption @ 75% 2,9 l/h
Other Features	<ul style="list-style-type: none">+ Insulation Class H+ Mechanical Protection IP 23+ Dimensions (L x W x H) 730 x 480 x 520 mm+ Dry Weight 80 kg

EA 80 GH



mase
GENERATORS