

1860

MG 15DT

ġ

6

1.1

CE

GEN SET S.p.a. Via Stazione,5 - 27030 Villanova D'Ardenghi (Pavia) Italy Tel. (+39) 0382-5091 - Fax (+39) 0382-509-244 E-mail: genset@genset.it - internet: //www.genset.it





Gen Set Features	MG 15DTSUPER SILENCED VOYAGER THREE-PHASE POWER GENERATOR / OUTPUT POWER 14 KVA THREE-PHASE / DIESEL ENGINE 1500 RPM+ Control panel on board with: - Safety shutdown in case of battery charger failure, high water temperature, low oil pressure, high alternator temperature. - Faults memory - Hourmeter - Start/Stop button - Circuit breaker and earth leakage circuit breaker for overload and short-circuit protection + Remote control (20mt.) with: - Start/Stop button - Generator running lamp
Noise Level	+ Lwa 87 (62 dB a 7 m)
AC Generator 50 Hz	 + Type: synchronous with AVR + Three-phase power (stand by): 14 kVA - 400 V + Three-phase power (prime): 12,7 kVA - 400 V + Power Factor: cos φ 0,8
Diesel Engine 1500 rpm	 + Type: Yanmar 3TNV88 - 3 cyl. 17,9 HP (13,2 kWm) - 1642 cm³ + Fuel: diesel + Cooling system: water + Starting system: electric + Fuel consumption @ 75%: 3,6 l/h
Other Features	 + Insulation Class: H + Ambient temperature: 40 °C + Altitude: 1000 mt + Mechanical Protection: IP 23 + Dimensions (L x W x H): 1440 x 650 x 810 mm + Dry weight: 485 kg

Generator set in designed to operate in ambient temperature up to 40 °C and 1000 mt altitude - For higher values of temperature and altitude please consult factory to check available power.

Specifications and pictures introduced here are not contractual and are subjected to change without prior notice.