

TOROIDAL TRANSFORMERS

POWER: from 20 to 30.000VA

CUSTOMIZABLE CHARACTERISTICS:



- Transformer or Auto-transformer
- Single-phase or three-phase
- Customized input / output voltages
- Multiple primaries and secondaries
- Terminal blocks
- Heat protection
- Portafuse on the wiring

TECHNICAL DATA:

- Continuous service
- Frequency: 50/60Hz
- Protection degree: IP00
- Heat insulation degree: B(130°C) / F(155°C)

STANDARD PRODUCTS:

- Power: from 50 to 500VA
- Input voltages: 230 VAC
- Output voltages: 0-12 VAC
0-24 VAC



Customized items on customer's request

| Code | Power (VA) | Dimensions in mm | | Weight (Kg) |
|---------|------------|------------------|--------|-------------|
| | | Diameter | Height | |
| | | D | H | |
| TOR0020 | 20 | 60 | 30 | 0,5 |
| TOR0030 | 30 | 70 | 30 | 0,6 |
| TOR0050 | 50 | 80 | 34 | 0,7 |
| TOR0100 | 100 | 95 | 44 | 1,1 |
| TOR0150 | 150 | 100 | 45 | 1,5 |
| TOR0200 | 200 | 110 | 50 | 1,9 |
| TOR0250 | 250 | 114 | 50 | 2,3 |
| TOR0300 | 300 | 130 | 50 | 2,6 |
| TOR0400 | 400 | 132 | 58 | 4,1 |
| TOR0500 | 500 | 132 | 70 | 4,3 |
| TOR0600 | 600 | 145 | 75 | 6,0 |
| TOR0800 | 800 | 145 | 80 | 6,8 |
| TOR1000 | 1000 | 150 | 80 | 7,2 |
| TOR1500 | 1500 | 180 | 80 | 10,0 |
| TOR2000 | 2000 | 185 | 100 | 13,0 |
| TOR2500 | 2500 | 185 | 105 | 14,0 |
| TOR3000 | 3000 | 215 | 100 | 18,0 |
| TOR4000 | 4000 | 220 | 105 | 19,0 |
| TOR5000 | 5000 | 245 | 110 | 25,0 |

Standard products

| Code | Power (VA) | Voltage VE/VU (V) | Dimensions in mm | | Weight (Kg) |
|-----------|------------|-------------------|------------------|--------|-------------|
| | | | Diameter | Height | |
| | | | D | H | |
| TOR005012 | 50 | 230 / 12 | 80 | 34 | 0,7 |
| TOR005024 | 50 | 230 / 24 | 80 | 34 | 0,7 |
| TOR010012 | 100 | 230 / 12 | 95 | 44 | 1,1 |
| TOR010024 | 100 | 230 / 24 | 95 | 44 | 1,1 |
| TOR015012 | 150 | 230 / 12 | 100 | 45 | 1,5 |
| TOR015024 | 150 | 230 / 24 | 100 | 45 | 1,5 |
| TOR020012 | 200 | 230 / 12 | 110 | 50 | 1,9 |
| TOR020024 | 200 | 230 / 24 | 110 | 50 | 1,9 |
| TOR030012 | 300 | 230 / 12 | 130 | 50 | 2,6 |
| TOR030024 | 300 | 230 / 24 | 130 | 50 | 2,6 |
| TOR040012 | 400 | 230 / 12 | 132 | 58 | 4,1 |
| TOR040024 | 400 | 230 / 24 | 132 | 58 | 4,1 |
| TOR050012 | 500 | 230 / 12 | 132 | 70 | 4,3 |
| TOR050024 | 500 | 230 / 24 | 132 | 70 | 4,3 |

* Over 5000VA dimensions and weights are on demand