

ELETRAS S.R.L.

since 1978

BP SERIES

PCB TRANSFORMERS

RESIN AND LOW PROFILE VERSION



100%
Made in Italy



POWER: from 2 to 45VA

CUSTOMIZABLE CHARACTERISTICS:

Customized input and output voltages
Multiple primaries and secondaries







EN61558-2-4



EN61558-2-6

TECHNICAL DATA:

Continuous service
Frequency: 50/60Hz
Protection degree: IP00
Heat insulation degree: B(130°C) / F(155°C)



Code	Power (VA)	Type	Dimensions in mm							
			Length A	Depth B	Height H	Pitch Y	Pitch X	Pitch Z	Boxes clamping D I	
2B6	2	B6	53	44	17	35	5	5	47.5	37.5
4B6	4	B6	53	44	19	35	5	5	47.5	37.5
6B6	6	B6	53	44	23	35	5	5	47.5	37.5
9B6	9	B6	53	44	29	35	5	5	47.5	37.5
9B7	9	B7	68	57	22	45	5	6	62.5	50
12B7	12	B7	68	57	25	45	5	6	62.5	50
15B7	15	B7	68	57	29	45	5	6	62.5	50
20B7	20	B7	68	57	32	45	5	6	62.5	50
25B7	25	B7	68	57	36	45	5	6	62.5	50
30B8	30	B8	86	70	37	52,5	5	7	75	60
45B8	45	B8	86	70	46	52,5	5	7	75	60