

PCB TRANSFORMERS

NON RESIN VERSION



100%



Made in Italy

POWER: from 1 to 200VA

CUSTOMIZABLE CHARACTERISTICS:

Customized input and output voltages

Multiple primaries and secondaries


Available also resin (R series)




EN61558-2-4




EN61558-2-6




Type 2



Type 3



Type 4



Type 5

TECHNICAL DATA:

Continuous service

Frequency: 50/60Hz

Protection degree: IP00

Heat insulation degree: B(130°C) / F(155°C)

Code	Power (VA)	Dimensions in mm					Core	Type
		Length A	Depth B	Height H	Pitch Y	Pitch X		
NP1+	1	30	25	22	20	5	10x10P	2
NP1,5+	2	30	25	25	20	5	10x15P	2
NP2+	2	30	25	27	20	5	10x18P	2
NG1	1	33	27	26	20	5	10x10G	2
NG1,5	2	33	27	31	20	5	10x15G	2
NG2	2	33	27	31	20	5	10x15G	2
NG2,5	3	33	27	33	20	5	10x18G	2
N3	3	40	34	30	25	5	13x13	2
N4	4	40	34	32	25	5	13x15	2
N4F6*	4	40	34	32	27,5	5	13x15	3
N4,5	5	40	34	37	25	5	13x20	2
N5	5	48	40	35	27,5	5	16x16	3
N6	6	48	40	39	27,5	5	16x16	3
N8	8	48	40	44	27,5	5	16x20	3
N10	10	48	40	45	27,5	5	16x25	3
N15	15	60	50	50	33	5	20x20	4
N20	20	60	50	55	33	5	20x25	4
N25	25	60	50	61	33	5	20x30	4
N30	30	68	58	66	35	5	22x30	5
N40	40	68	58	60	35	5	22x35	5
N50	50	75	63	64	40	7,5	25x30	3
N60	60	75	63	69	40	7,5	25x35	3
N70	70	75	63	74	40	7,5	25x40	3
N100	100	84	70	80	45	7,5	28x40	4
N150	150	96	80	90	56	10	32x40	3
N200	200	96	80	100	56	10	32x50	3

+ NP items have no insulating shells protections

* 6-hole version