




47 280

LUMENS



LUMAPHORE® LED 400XL – 230V

NEW



The LUMAPHORE® 400 XL is the latest addition to the LUMAPHORE® LED range. With increased ground level lighting, it contains 4 high-power COB LEDs in a translucent polycarbonate casing. The LUMAPHORE® LED 400XL provides 47,000 Lumens at 420 W, a ratio of 110 lumens/watt. It is a versatile and desirable lamp for :

- Road marking operations
- Road surfacing operations
- Emergency services
- Civil Security
- Civil Engineering operations
- Motorway operations

Benefits :

- 2400 m2 lighting from 420 Watts
- Powerful ground level lighting
- 100% instant illumination
- Light
- Robust : ABS, polycarbonate casing
- Weather resistant
- Superbly versatile for use in many environments





LUMAPHORE® LED 400 XL – Technical data

Electrical Specifications

No. Of LED modules	8 + 4 COB
No. Of LEDs per module	88
Total Lighting Output	420 W
Power of electricity supply	445 W
Connecting cable 3x1.5 ² head	7 m
Average life of LEDs	50000 hrs
Immediate illumination	yes

Safety Specifications


Protection index	IP44
Wind resistance	NC
Mast with guy wires	Yes
Temperature range for use	-15°/+40°

Photometric Specifications

Area of illumination	2400 m ²
Colour temperature	5000 °K
Lumens/module/COB	4060/3700
total Lumens	47280
Color rendering index	> 82

Mechanical Specifications

Diameter	22,5 cm
Length	91 cm
Weight	6,5 Kg
Optimal height for use	3 à 4 m
Average assembly time	2 mn



Honda Generator EU10i – 1000 W



Flight case



180/360 and/or On/Off

Accessories Available

Telescopic mast with or without winch
Carry Bag
Suspension cradle
Support with 15° angle
Switch 180/360 and/or ON/OFF
1000 W Generator

