

T16F

MECCALTE spa - Via Roma, 20 - 36051 CREAZZO (VI) ITALIA
 Tel. +39 0444/396111 - Fax +39 0444/396166 - e-mail : info@meccalte.it
 web site: www.meccalte.com

3 PHASE 2 POLE IP 23

CHARACTERISTICS

POWER 230/400 V at 3000 RPM - 50 Hz

Type	CL. H ($\Delta T=125^{\circ}\text{C}$)						CL. F ($\Delta T=105^{\circ}\text{C}$)		CL. H ($\Delta T=125^{\circ}\text{C}$)		T.H.D. %
	THREE-PHASE		MOTOR STARTING CAPABILITY KVA	EFFICIENCY			THREE-PHASE		SINGLE-PHASE		
	KVA	KW COS φ 0,8		2/4 %	3/4 %	4/4 %	KVA	KW COS φ 0,8	KVA COS φ 1	MOTOR STARTING CAPABILITY KVA	
T16F-130	6	4,8	20	75,5	79,5	79,8	5,5	4,4	4	16	< 5
T16F-160	7,5	6	26	78	82,5	82	6,8	5,4	5	19,5	< 5

POWER 277/480 V at 3600 RPM - 60 Hz

Type	CL. H ($\Delta T=125^{\circ}\text{C}$)						CL. F ($\Delta T=105^{\circ}\text{C}$)		CL. H ($\Delta T=125^{\circ}\text{C}$)		T.H.D. %
	THREE-PHASE		MOTOR STARTING CAPABILITY KVA	EFFICIENCY			THREE-PHASE		SINGLE-PHASE		
	KVA	KW COS φ 0,8		2/4 %	3/4 %	4/4 %	KVA	KW COS φ 0,8	KVA COS φ 1	MOTOR STARTING CAPABILITY KVA	
T16F-130	7,2	5,8	24,5	76,5	80	80,3	6,5	5,3	5	20	< 5
T16F-160	9	7,2	31	79	83	82,5	8,2	6,6	6	23,5	< 5

Type	J (Kgm ²)	Weight (Kg)	Air Volume (m ³ /min)		Noise dB(A)			
			50 Hz		50 Hz		60 Hz	
			50 Hz	60 Hz	7m	1m	7m	1m
T16F-130	0,0129	30,5	3,4	4,3	60	78	62	80
T16F-160	0,0156	34,5	3,4	4,3	60	78	62	80

Type		T16F-130	T16F-160
Rating "H" class	kVA 50 Hz	6	7,5
Direct - axis synchronous reactance	X _d %	331	287
Direct - axis transient reactance	X' _d %	44,5	44
Direct - axis subtransient reactance	X'' _d %	21,8	21,5
Quadrature - axis synchronous reactance	X _q %	109	111
Quadrature - axis transient reactance	X' _q %	109	111
Quadrature-axis subtransient reactance	X'' _q %	40,6	41
Negative - sequence reactance	X ₂ %	23,6	21,5
Zero sequence reactance	X ₀ %	8,9	8,2
Transient time constant	T' _d (ms)	41	38
Subtransient time constant	T'' _d (ms)	10	9
Armature time constant	T _α (ms)	5	6
Open circuit time constant	T' _{do} (s)	0,8	0,9
Short - circuit ratio	K _{cc}	0,86	0,9
Stator winding resistance	Ω	1,5	1,15

REGULATOR COMPOUND TRANS.	PARALLEL DEVICE	THERMAL PROTECTION			HEATERS	MECHANICAL PROTECTION		
		PTC	BIMET DEVICE	PT100		IP21	IP23	IP45
●		<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>		●	<input type="checkbox"/>


● = Standard

□ = Optional



OVERALL SIZE, STANDARD TYPE


dimensions in mm



FORM	CG	
	130	160
B14	187	172
B9	189	174
J609a	188	173
J609b	188	173

OVERALL SIZE WITH ELECTRIC PANELBOARD TYPE

dimensions in mm



SOCKETS TYPE	P	THERMAL PROTECTOR	M	WITH BATTERY CHARGING	CB
AMERICAN	4	OPTIONAL	6	OPTIONAL	30
FRENCH	10				
SCHUKO	13				
CEE	50				