



EURARC 322 230V/400V



Overview

EURARC 322 230V/400V

cod. 817014

MMA stick electrode welding machine in alternating current (AC).

Stepless regulation of welding current.

With thermostatic protection.

The model has double secondary voltage for use also with basic and rutile electrodes.

Technical data

CODE	CODE 817014	A_{60%}_{40°C}	CURRENT AT 60% 125 A	IP	PROTECTION DEGREE IP22
V_{1PH}	SINGLE PHASE MAINS VOLTAGE 230 V	V₀	MAX NO LOAD VOLTAGE 52 - 76 V	W_H L	DIMENSIONS 69 - 39 - 48 cm
V_{2PH}	DOUBLE PHASE MAINS VOLTAGE 400 V	P_{MAX}	MAX ABSORBED POWER 9 kW	kg	WEIGHT 37 kg
F	MAINS FREQUENCY 50 / 60 Hz	P_{60%}	ABSORBED POWER AT 60% 3,5 kW	BAR CODE	EAN CODE 800489785093 1
A_{MIN} MAX	CURRENT RANGE 45 - 250 A	φ	POWER FACTOR (cosphi) 0,4	GRID	PIECES/PALLET 12 pz/pallet
A_{MAX} 40°C	MAX CURRENT 250 A - 15 %	φ_{AC} MIN/MAX	D. USABLE ELECTRODES IN AC 1,6 - 5 mm		