



EURARC 522 230V/400V



Overview

EURARC 522 230V/400V

cod. 817018

MMA stick electrode welding machine in alternating current (AC).

Stepless regulation of welding current.

With thermostatic protection.

The model has double secondary voltage for use also with basic and rutile electrodes.

Technical data

CODE	CODE 817018	A_{60%}_{40°C}	CURRENT AT 60% 265 A	IP	PROTECTION DEGREE IP22
V_{1PH}	SINGLE PHASE MAINS VOLTAGE 230 V	V₀	MAX NO LOAD VOLTAGE 52 - 71 V	W^H_L	DIMENSIONS 95 - 49 - 68 cm
V_{2PH}	DOUBLE PHASE MAINS VOLTAGE 400 V	P_{MAX}	MAX ABSORBED POWER 15 kW	kg	WEIGHT 81 kg
F	MAINS FREQUENCY 50 / 60 Hz	P_{60%}	ABSORBED POWER AT 60% 11 kW	BAR CODE	EAN CODE 800489785092 4
A_{MIN}_{MAX}	CURRENT RANGE 40 - 400 A	∅	POWER FACTOR (cosphi) 0,7	Grid	PIECES/PALLET 6 pz/pallet
A_{MAX}_{40°C}	MAX CURRENT 350 A - 35 %	∅_{AC}_{MIN/MAX}	D. USABLE ELECTRODES IN AC 1,6 - 6 mm	Grid	PIECES/PALLET - B 3 pz/pallet - B