



LINEAR 280 230-400V



Aluminium

Overview

LINEAR 280 230-400V

cod. 818002

MMA, rectified, electrode welding machine in direct current (DC). Stepless regulation of welding current. Use with a wide range of electrodes: rutile, basic, stainless steel, cast iron and aluminium.

Technical data

CODE	CODE 818002	A_{60%}_{40°C}	CURRENT AT 60% 140 A	IP	PROTECTION DEGREE IP22
V_{3PH}	THREE PHASE MAINS VOLTAGE 230 / 400 V	V₀	MAX NO LOAD VOLTAGE 62 V	W^H_L	DIMENSIONS 89 - 46 - 59 cm
F	MAINS FREQUENCY 50 / 60 Hz	P_{MAX}	MAX ABSORBED POWER 8 kW	kg	WEIGHT 65 kg
A_{MIN}_{MAX}	CURRENT RANGE 50 - 260 A	P_{60%}	ABSORBED POWER AT 60% 5 kW	BAR CODE	EAN CODE 800489731251 4
A_{MAX}_{40°C}	MAX CURRENT 190 A - 35 %	∅	POWER FACTOR (cosphi) 0,6	Grid	PIECES/PALLET 6 pz/pallet
A_{MAX}_{40°C}	MAX CURRENT 230 A - 25 %	∅_{DC}_{MIN/MAX}	D. USABLE ELECTRODES IN DC 1,6 - 5 mm	Grid	PIECES/PALLET - B 3 pz/pallet - B