



LINEAR 340 230-400V



Overview

LINEAR 340 230-400V

cod. 819020

MMA, rectified, electrode welding machine in direct current (DC). Stepless regulation of welding current. Use with a wide range of electrodes: rutile, basic, stainless steel, cast iron and aluminium.

Technical data

CODE	CODE 819020	A 60% 40°C	CURRENT AT 60% 180 A	IP	PROTECTION DEGREE IP22
V 3PH	THREE PHASE MAINS VOLTAGE 230 / 400 V	V 0	MAX NO LOAD VOLTAGE 65 V	W H L	DIMENSIONS 89 - 46 - 59 cm
F	MAINS FREQUENCY 50 / 60 Hz	P MAX	MAX ABSORBED POWER 11,5 kW	kg	WEIGHT 80 kg
A MIN MAX	CURRENT RANGE 60 - 320 A	P 60%	ABSORBED POWER AT 60% 7 kW	BAR CODE	EAN CODE 800489731252 1
A MAX 40°C	MAX CURRENT 260 A - 35 %	φ	POWER FACTOR (cosphi) 0,6	Grid	PIECES/PALLET 6 pz/pallet
A MAX 40°C	MAX CURRENT 320 A - 25 %	φ DC MIN/MAX	D. USABLE ELECTRODES IN DC 2 - 6 mm	Grid	PIECES/PALLET - B 3 pz/pallet - B