



Perkins

CARATTERISTICHE - SPECIFICATIONS CARACTERISTIQUES - SPEZIFIKATION	MPL 550 S	MPL 700 S	MPL 900 S	MPL 1125 S
POTENZA A.C. - A.C. OUTPUT 50Hz-3~ PUISSANCE A.C. - LEISTUG A.C. 400V MAX. CON	550 KVA 500 KVA	700 KVA 650 KVA	900 KVA 800 KVA	1125 KVA 1022 KVA
FATTORE DI POTENZA - POWER FACTOR FACTEUR DE PUISSANCE - LEISTUGFAKTOR	0,8	0,8	0,8	0,8
ALTERNATORE - ALTERNATOR ALTERNATEUR - GENERATEUR	SINCRONO - SYNCHRONOUS SYNCHRONE - SYNCHRON	SINCRONO - SYNCHRONOUS SYNCHRONE - SYNCHRON	SINCRONO - SYNCHRONOUS SYNCHRONE - SYNCHRON	SINCRONO - SYNCHRONOUS SYNCHRONE - SYNCHRON
MOTORE - ENGINE - MOTEUR - ANTRIEBSMOTOR	PERKINS 2506C-E15TAG2	PERKINS 2806A-E18TAG2	PERKINS 4006-23TAG3A	PERKINS 4008 TAG2A
RAFFREDDAMENTO MOTORE - COOLING REFROIDISSEMENT - KÜHLUNG	ACQUA - WATER COOLED EAU - WASSERGEKÜHLT	ACQUA - WATER COOLED EAU - WASSERGEKÜHLT	ACQUA - WATER COOLED EAU - WASSERGEKÜHLT	ACQUA - WATER COOLED EAU - WASSERGEKÜHLT
CILINDRATA - DISPLACEMENT C.C CYLINDREE - HUBRAUM n° cil.	15200 6	18100 6	22921 6	30561 8
POTENZA MAX - MAX POWER HP PUISSANCE MAXI - MAX LEISTUG	664	852	1054	1290
GIRI/MIN - R.P.M. TOURS/MIN - DREHZAHL U / MIN.	1500	1500	1500	1500
ALIMENTAZIONE - FUEL ALIMENTATION - KRAFTSTOFF	DIESEL	DIESEL	DIESEL	DIESEL
CAPACITA' SERBATOIO - TANK CAPACITY CON.RESERVOIR - TANKINHALT Lt.	370	370	520	520
AUTONOMIA 3/4 CARICO - 3/4 LOAD OPER.HOURS AUTONOMIE 3/4 CHARGE - LAUFZEIT BEI 3/4 AUS h	4,5	3,8	4,3	2,6
AVVIAMENTO - STARTING DEMARRAGE - STARTSYSTEM	ELETTRICO - ELECTRIC ELECTRIQUE - ELEKTROSTART	ELETTRICO - ELECTRIC ELECTRIQUE - ELEKTROSTART	ELETTRICO - ELECTRIC ELECTRIQUE - ELEKTROSTART	ELETTRICO - ELECTRIC ELECTRIQUE - ELEKTROSTART

QUADRO ELETTRICO MANUALE -
MANUAL CONTROL PANEL -
TABLEAU DES COMMANDES MANUEL -
HANDSCHALTAFEL

MPL
550 S
700 S
900 S
1125 S



DIMENSIONI - SIZES - DIMENTIONS - MAßE				
PESO - WEIGHT - POIDS - GEWICHT				
POTENZA SONORA - NOISE POWER -				
LEVEL PUISSANCE ACOUSTIQUE - SCHALLEISTUNGSPEGEL				
	MPL 550 S	MPL700 S	MPL 900 S	MPL1125 S
LxWxH	4730x1800x3080	4730x1800x3080	6260x2040x3300	6690x2400x3590
kg	6300	6800	7500	9000
LwA	95	95	95	95