

GenSet



WELDBABY 180



GEN SET S.p.a.

Via Stazione,5 - 27030 Villanova D'Ardenghi (Pavia) Italy
Tel. (+39) 0382-5091 - Fax (+39) 0382-509-244
E-mail: genset@genset.it - internet: [//www.genset.it](http://www.genset.it)

WELDBABY 180

PORTABLE ENGINE DRIVEN WELDER / DELIVERS **165 A** OF DC WELD OUTPUT /
SINGLE-PHASE AUXILIARY POWER AVAILABLE / PETROL ENGINE **4000 RPM**

| | |
|-----------------------------------|---|
| Gen Set Features | Welding processes: SMAW (stick) + Low oil level cut out device + 1 x 16 A, 110 V DC- single-phase EEC socket + 1 x 16 A, 230 V DC- single-phase EEC socket + 3 x circuit breakers + Automatic idle device when no load is connected |
| Noise Level | + Lwa 98 |
| DC Welding | + Duty Cycle @ 60% 165 A - 24 V + Output range 40 A - 165 A + Open Circuit Voltage 70 V + Max welding rod 4 mm |
| DC Generator | + Type: synchronous with PMG + Single-phase power (Prime Power): 1 kVA - 230 V DC + Single-phase power (Prime Power): 0,5 kVA - 110 V DC + Power factor: $\cos \varphi$ 0,8 |
| Petrol Engine 4000 rpm | + Type: Honda GX 200 OHV - 1 cyl. - 7,2 HP (5,3 kWm) - 196 cm ³ + Fuel: Petrol + Cooling system: air + Starting system: manual recoil + Fuel tank capacity: 3,8 l + Fuel consumption @ 75%: 1,8 l/h |
| Other Features | + Insulation Class: H + Ambient temperature: 40 °C (*) + Altitude: 1000 mt (*) + Mechanical Protection: IP 23 + Dimensions (L x W x H): 510 x 440 x 460 mm + Dry weight: 35 kg |

(*) - For altitude and temperature values higher than those listed above, please consult the manufacturer to verify the available power.