

# MG 10000 S-KL



Warning Lights



Emergency Stop



40 lt Fuel Tank



**Stage V**

We offer now what others will do tomorrow.



**GenSet s.p.a.**

Via Stazione 5 - 27030  
Villanova d'Ardenghi (PV) - Italy  
Phone: +39-0382-5091

commerciale@genset.it  
www.genset.it

 **GenSet**  
Next Gen technology  
for top business.

**SILENCED POWER GENERATOR**  
**OUTPUT POWER 10 KVA SINGLE-PHASE**  
**DIESEL ENGINE 1500 RPM**  
**FUEL TANK 40 LT**

<b>Standard Features</b>	<ul style="list-style-type: none"> <li>• Auto engine protection shutdown system with warning lights for:             <ul style="list-style-type: none"> <li>- battery charger failure</li> <li>- high water temperature</li> <li>- low fuel level</li> <li>- low oil pressure</li> </ul> </li> <li>• 1 x 230V - 32A EEC single-phase socket</li> <li>• 1 x 230V single-phase output</li> <li>• 12V built-in battery</li> <li>• Power output protection</li> <li>• Earth Leakage Circuit Breaker</li> <li>• Voltmeter</li> <li>• Hourmeter</li> <li>• Emergency stop button</li> <li>• Fork-lift pockets</li> </ul>
<b>Options</b> available as factory options	<ul style="list-style-type: none"> <li>• Versions with different voltages</li> <li>• 60Hz version</li> </ul>
<b>Accessories</b> on request	<ul style="list-style-type: none"> <li>• Trolley: two wheels and handles</li> </ul>
<b>Noise level</b>	<ul style="list-style-type: none"> <li>• Lwa 95 (70 dB at 7 mt)</li> </ul>
<b>AC generator - 50Hz</b>	<ul style="list-style-type: none"> <li>• Type: synchronous</li> <li>• Single-phase power (stand-by): 10kVA - 230V</li> <li>• Single-phase power (prime): 9kVA - 230V</li> <li>• Power Factor: <math>\cos \phi</math> 0,8</li> </ul>
<b>Diesel Engine</b> 1500 rpm	<ul style="list-style-type: none"> <li>• Type: Kubota D1105 - 3 cyl. - 1123 cm<sup>3</sup></li> <li>• Max power: 12,7 hp (9,5 kWm)</li> <li>• Starting system: electric (12Vdc)</li> <li>• Cooling system: water</li> <li>• Fuel consumption @ 75%: 2 lt/h</li> </ul>
<b>Other features</b>	<ul style="list-style-type: none"> <li>• Insulation Class: H</li> <li>• Ambient temperature: 40 °C (*)</li> <li>• Altitude: 1000 m (*)</li> <li>• Mechanical Protection: IP 23</li> <li>• Fuel tank capacity: 40 lt</li> <li>• Dimensions (L x W x H): 1357 x 707 x 942 mm</li> <li>• Dry weight: 350 kg</li> </ul>

(\*) - For altitude and temperature values higher than those listed above, please consult the manufacturer to verify the available power.  
In line with our continued development, innovation and voice of customer program, we reserve the right to change data without notice.