

MG 10/8 SS-K



Instrument panel



Rapid access for maintenance



Lifting eye



Stage V

We offer now what others will do tomorrow.



GenSet s.p.a.

Via Stazione 5 - 27030
Villanova d'Ardenghi (PV) - Italy
Phone: +39-0382-5091

commerciale@genset.it
www.genset.it

GenSet
Next Gen technology
for top business.

SUPER SILENCED POWER GENERATOR
OUTPUT POWER 10 KVA THREE-PHASE AND 6 KVA SINGLE-PHASE
DIESEL ENGINE 3000 RPM
FUEL TANK 30 LT

<p>Standard Features</p>	<ul style="list-style-type: none"> • 12V battery • 1 x 400V - 16A three-phase EEC socket • 1 x 230V - 32A single-phase EEC socket • 1 x 230V - 16A single-phase EEC socket • Thermal protection • Earth leakage circuit breaker • Emergency stop button • Voltage selector • Voltmeter • Hourmeter • Central lifting eye • Foreseen for AMF-ATS or Remote control operation • Glow plug preheating lamp • Auto engine protection shutdown system with warning lights for: <ul style="list-style-type: none"> - battery charger failure - high water temperature - low oil pressure - low fuel level
<p>Options available as factory options</p>	<ul style="list-style-type: none"> • Versions with different voltages • 60Hz version • Spark arrester muffler • Engine heater
<p>Accessories on request</p>	<ul style="list-style-type: none"> • Remote control unit with 20 mt cable • AMF / ATS panel • Trolley: two-wheels and handles
<p>Noise level</p>	<ul style="list-style-type: none"> • Lwa 90 (65 dB a 7 mt)
<p>AC generator - 50Hz</p>	<ul style="list-style-type: none"> • Type: synchronous • Single-phase power (stand-by): 10 kVA - 400 V • Single-phase power (stand-by): 6 kVA - 230 V • Power Factor: $\cos \phi$ 0,8
<p>Diesel Engine 3000 rpm</p>	<ul style="list-style-type: none"> • Type: Kubota D 722 - 3 cyl. - 719 cm³ • Max power: 19 HP (14 kWm) • Starting system: electric (12Vdc) • Cooling system: water • Fuel tank capacity: 30 lt • Fuel consumption @ 75%: 3,3 lt/h
<p>Other features</p>	<ul style="list-style-type: none"> • Insulation Class: H • Ambient temperature: 40 °C (*) • Altitude: 1000 mt (*) • Mechanical Protection: IP 23 • Dimensions (L x W x H): 1360 x 675 x 860 mm • Dry weight: 350 kg

(*) - For altitude and temperature values higher than those listed above, please consult the manufacturer to verify the available power.
 In line with our continued development, innovation and voice of customer program, we reserve the right to change data without notice.