

H 500



LS208

208 CM³ / 4,1 KW

3600 RPM/MIN

TIPO MOTORE

4 TEMPI OHV

ENGINE TYPE

**4 STROKES,
SINGLE CYLINDER OHV**

SISTEMA AVVIAMENTO

**MANUALE
O ELETTRICO**

(in optional)

STARTING SYSTEM

**MANUAL
OR ELECTRIC**

(in optional)

CAPACITA' DI CARICO
(PIANO/PENDENZA)

500 KG / 350 KG

MAX PAYLOAD

(FLAT/SLOPE)

500 KG / 350 KG

PENDENZA SUPERABILE

20%

MAX GREADABILITY

20%

PESO NETTO

310 KG

NET WEIGHT

310 KG

DIMENSIONI INGOMBRO

147,8x80x125 CM

OVERALL DIMENSIONS

147,8x80x125 CM

DIMENSIONI CASSONE

105x72x51 CM

TIPPER DIMENSIONS

105x72x51 CM

SISTEMA DI RIBALTAMENTO

IDRAULICO

PRESSIONE 160BAR

PORTATA 12,6 LT/M

CILINDRO IDRAULICO

DOPPIO EFFETTO

TIPPING SYSTEM

HYDRAULIC

PRESSURE - 160 BAR

MAX PUMPFLOW - 12,6 L/MIN

DOUBLE EFFECT

HYDRAULIC CYLINDER

TAGLIA CINGOLI

180x60x38

RUBBER TRACK SIZE

180x60x38