

H 500 C



LS208
208 CM³ / 4,1 KW
3600 RPM/MIN

TIPO MOTORE
4 TEMPI OHV

ENGINE TYPE
**4 STROKES,
SINGLE CYLINDER OHV**

SISTEMA AVVIAMENTO
**MANUALE
O ELETTRICO**
(in optional)

STARTING SYSTEM
**MANUAL
OR ELECTRIC**
(in optional)

CAPACITA' DI CARICO
(PIANO/PENDENZA)
500 KG / 350 KG

MAX PAYLOAD
(FLAT/SLOPE)
500 KG / 350 KG

PENDENZA SUPERABILE
20%

MAX GREADABILITY
20%

PESO NETTO
395 KG

NET WEIGHT
395 KG

DIMENSIONI INGOMBRO
147,8x83,5x125 CM

OVERALL DIMENSIONS
147,8x83,5x125 CM

DIMENSIONI CASSONE
105x72x51 CM

TIPPER DIMENSIONS
105x72x51 CM

SISTEMA DI RIBALTAMENTO
**IDRAULICO
PRESSIONE 160BAR
PORTATA 12,6 LT/M
CILINDRO IDRAULICO
DOPPIO EFFETTO**

TIPPING SYSTEM
**HYDRAULIC
PRESSURE - 160 BAR
MAX PUMPFLOW - 12,6 L/MIN
DOUBLE EFFECT
HYDRAULIC CYLINDER**

TAGLIA CINGOLI
180x60x38

RUBBER TRACK SIZE
180x60x38