

W350E



BLDC "HIGH TORQUE" SERVOMOTOR

TIPO MOTORE

MOTORI BRASHLESS DC ENGINE TYPE

CON PROTEZIONE SOVRACCARICO

POTENZA (HP/KW): 0,82/0,6

BATTERIA A LITIO: 48V 50AH

ENGINE TYPE

ELECTRIC

WHIT OVERLOAD PROTECTION

POWER (HP/KW): 0,82/0,6

LITHIUM BATTERY: 48V 50AH

VELOCITA' Avanti | Retro

0,5-4,46 km/h | 0,6-2,3 km/h

FORWARD - BAKWARD SPEED

0,5-4,46 km/h | 0,6-2,3 km/h

RIBALTAMENTO

MANUALE

TIPPING SYSTEM

MANUAL

CAPACITA' DI CARICO

(PIANO/PENDENZA)

350 KG / 200 KG

MAX PAYLOAD

(FLAT/SLOPE)

350 KG / 200 KG

PENDENZA SUPERABILE

(a pieno carico)

30%

MAX GREADABILITY

(full load)

30%

PESO NETTO

160 KG

NET WEIGHT

160 KG

DIMENSIONI INGOMBRO

155,5x86x101 CM

OVERALL DIMENSIONS

155,5x86x101 CM

DIMENSIONI CASSONE

115x38,6x80/56 CM

TIPPER DIMENSIONS

115x38,6x80/56 CM

SISTEMA DI RIBALTAMENTO

MANUALE CON PISTONE A GAS

TIPPING SYSTEM

MANUAL WITH GAS PISTON

RUOTE (anteriori / posteriori)

16x6,5-8" | 13x5,00-6"

WHEELS (front / rear)

16x6,5-8" | 13x5,00-6"

AUTONOMIA MEDIA / TEMPO DI RICARICA

± 10 H | ± 3,5H

WORKING TIME / RELOAD TIME

± 10 H | ± 3,5H