

# MG 3000 I-BE 3,1 LT



3000 rpm engine



Frontal panel



3,1 Lt Fuel Tank



Stage V

We offer now what others will do tomorrow.



**GenSet s.p.a.**

Via Stazione 5 - 27030  
Villanova d'Ardenghi (PV) - Italy  
Phone: +39-0382-5091

commerciale@genset.it  
www.genset.it

 **GenSet**  
Next Gen technology  
for top business.

**PORTABLE SINGLE-PHASE POWER GENERATOR**  
**OUTPUT POWER 3 kVA**  
**PETROL ENGINE 3000 RPM**  
**3,I LT FUEL TANK**

Standard Features	<ul style="list-style-type: none"> <li>• Low oil level shutdown device</li> <li>• 2 x 230 V - 50 Hz single-phase Schuko socket protected by circuit breaker</li> </ul>
Noise level	<ul style="list-style-type: none"> <li>• Lwa 97 (72 dB a 7 mt)</li> </ul>
AC generator - 50Hz	<ul style="list-style-type: none"> <li>• Type: synchronous</li> <li>• Single-phase power (max.): 3 kVA - 230 V</li> <li>• Power Factor: <math>\cos \phi</math> 0,8</li> </ul>
Petrol Engine 3000 rpm	<ul style="list-style-type: none"> <li>• Type: Briggs &amp; Stratton XR750 - 1 cyl. - 4,3 HP (3,2 kWm) - 163 cm<sup>3</sup></li> <li>• Cooling system: air</li> <li>• Starting system: recoil</li> <li>• Fuel tank capacity: 3,1 lt</li> <li>• Fuel consumption @ 75%: 1,4 lt/h</li> </ul>
Other features	<ul style="list-style-type: none"> <li>• Insulation Class: H</li> <li>• Ambient temperature: 40 °C (*)</li> <li>• Altitude: 1000 mt (*)</li> <li>• Mechanical Protection: IP 23</li> <li>• Dimensions (L x W x H): 610 x 360 x 410 mm</li> <li>• Dry weight: 38 kg</li> </ul>

(\*) - For altitude and temperature values higher than those listed above, please consult the manufacturer to verify the available power.  
 In line with our continued development, innovation and voice of customer program, we reserve the right to change data without notice.