



Specifications

WP Sine 12 V / 600 W

07-04-2023

NUMERO DELL'ARTICOLO

61120600

WP SINE-12 / 600

USCITA CA

Power (continuous)	600 W
Power (peak 500 ms)	800 W
Output Voltage	230 V
Output frequency	50 Hz
Transfer Switch	No
Total harmonic distortion (THD)	<5% pure sine wave

INGRESSO DC

Nominal battery voltage	12 V
Voltage range	10.5 - 15.5 VDC
Input power	57 A
Consumption (no load)	0.8 A base

USCITA CC

5 V USB Phone charger	1000 mA
-----------------------	---------

DISPLAY

LED indicator	Yes Power / Fault
Digital display	Not applicable

PROTEZIONE E CARATTERISTICHE

Warning low input voltage	11.2 V
Shutdown low battery voltage	10.5 V
Recovery after low battery voltage	11.8 V
Shutdown battery voltage too high	15.5 V
Warning too much power	Not applicable
Shutdown too much power	Yes
Short circuit too much power	Yes
Temperature warning	Not applicable
Thermal protection (shutdown)	Yes
Conforms to	Directive EMC 2004/108/EC Low voltage directive 2006/95/EC
Operating temperature range	-20 - 55°C (derating above 40 ° C)
Relative humidity in operation	95 % without condensation

Ventilation

Dimensions L x W x H [mm]

Weight

Battery connector

AC-output

Warranty

Forced cooling

175 x 200 x 90 mm

1.73 kg

M5 studs

1 Schuko / UK socket

2 years