



# Specifications

## WP Sine 24 V / 2000 W

30-05-2023

### NUMERO DELL'ARTICOLO

61142500

WP Sine 24 V / 2000 W

### USCITA CA

Power (continuous)	2000 W
Power (peak 500 ms)	4000 W
Output Voltage	230 V
Output frequency	50 Hz
Transfer Switch	No
Total harmonic distortion (THD)	<5% pure sine wave

### INGRESSO DC

Nominal battery voltage	24 V
Voltage range	21 - 31 VDC
Input power	93.5 A
Consumption (no load)	1.6 A typical

### USCITA CC

5 V USB Phone charger	2100 mA
-----------------------	---------

### DISPLAY

LED indicator	Yes
Digital display	Input voltage / current, output power

### PROTEZIONE E CARATTERISTICHE

Warning low input voltage	22.4 VDC
Shutdown low battery voltage	21.0 VDC
Recovery after low battery voltage	23.6 VDC
Shutdown battery voltage too high	31.0 VDC
Warning too much power	Yes
Shutdown too much power	Yes
Short circuit too much power	Yes
Temperature warning	Yes
Thermal protection (shutdown)	Yes

Conforms to

EC Council Directive 2004/108/EC Electromagnetic Compatibility Registration No: NTC 1310 406E & E-marking

Operating temperature range

-20 - 55°C (derating above 40 ° C)

Relative humidity in operation

95%, non-condensing

Ventilation	Forced cooling
Dimensions L x W x H [mm]	230 x 416 x 112
Weight	5.5 kg
Battery connector	M6 Studs
Earth terminal	M6 Studs
AC-output	2 Schuko sockets
Warranty	2 years