



PUMA 256



INCLUDED

Power Supply	99820061 230V · (No accessories)
MIG Torch	23000425 · MIG 25 · 3m
Ground cable	43210132 · 25mm ² · 3m
Pressure regulator	22905049 mini CO ₂ /Argon · 2 manometers
Adaptor for gas bottles	22910014

	PUMA 256		
Input Voltage	(1ph) 230V ± 10% 50/60Hz		
	MIG	MMA	TIG
Power 60%	5,6 KW	5,6 KW	5,3 KW
U _o	35 V	55 V	55 V
Amp. Min-Max	30 ÷ 250 A	20 ÷ 200 A	10 ÷ 250 A
Duty Cycle 40°	250A @ 30%	200A @ 35%	250A @ 30%
Ø Steel	0,8 ÷ 1,0 mm	-	-
Ø Stainless Steel	0,8 ÷ 1,0 mm	-	-
Ø Aluminium	1,0 ÷ 1,2 mm	-	-
Ø Flux core	1,0 ÷ 1,2 mm	-	-
Ø CuSi ₃	0,8 mm	-	-
Ø E	-	1,6 ÷ 4 mm	-
Electrode Type	-	6013 Rutile · 7018 Basic	-
Insulation	H		
Protection degree	IP23		
Dim. (LxWxH)	450x840x710 mm		
Box (LxWxH)	365x895x650 mm		
Weight box/net	32 / 30 Kg		
Part number	99820061K		

PUMA 
MIG INVERTER RANGE