


The **NOMAD POWER PRO 700** is a lithium-based power pack that combines 3 functions:

- **Booster for 12 V vehicles** (*car, SUV, van, tractor, boat*).
- **Autonomous power supply for all kinds of electrical appliances.**
- **Emergency lamp.**

LITHIUM BATTERY BOOSTER

Its **lithium** battery gives it an exceptional power-to-size ratio (*starting current: 600 A*).

It starts vehicles equipped with a discharged 12 V battery (*liquid, gel, AGM, Start&Stop*) in a few seconds ( *do not start Lithium LiFePO₄ batteries with this booster, battery voltages not compatible*).

START 										
12 V PETROL & DIESEL										

SAFETY START

The **smart jump lead** protects both the battery and the vehicle's electronics:

- Anti sparks technology,
- Protection against short-circuits,
- Protection against polarity reversal,
- Protection against excessive starting currents,
- Protection against booster temperature increases.

MOBILE ENERGY SOURCE

Its powerful storage capacity (*6 Ah*) brings comfort and tranquility to the daily need to stay connected (*phone, tablet, computer*).

Equipped with:

- **2 ports USB 5 V - 2.1 A / 5/9/12 V - 2 A + 1 entrée/sortie USB Type C** for charging smartphone, tablet, GPS, etc.
- **1 output port 15 V - 10 A**, ideal for camping, to supply a 12 V electrical appliance (*cool box, fan, etc*).

ASSIST LAMP FUNCTION

Auxiliary light (*1 led*) with 3 lighting modes: normal, strobe, SOS.

POCKET SIZE

Lightweight (*820 g*) and **compact**, it will ideally fit in the glove box or empty pocket of the vehicle or in a travel bag.



Charging LED



Supplied with accessories:



Smart jump lead













micro USB cable



Charger 230 Vac / 5 Vdc



Charging cable
USB type C

STARTING						EQUIPMENT					INPUT / OUTPUT				POWER BANK	LED	DIMENSIONS			
Lithium		I				J3s	SMART CABLE 			CABLES 			INPUT 	OUTPUT 						
Capacity per cell	Full charge	Start	Cranking CC	Peak Battery	USB-C					MICRO USB Type B	Lightning	Type C		12 V	15 V					
6 Ah 92.5 Wh	9 h	600 A	1500 A	2000 A	14000 J	✓	✓	—	✓	✓	—	Type C 5V-3A	3	Type C 5V-2.1A	—	10 A	✓	3 modes: Light SOS SPOT	22.8 x 10 x 3.8	0.820