

Lightweight and easy to use, these torches offer great manoeuvrability for smooth welding. The moulded handle provides optimum grip for a perfect weld. Particularly recommended for MMA machines with TIG LIFT function.

FEATURES

SR 17 Valve

Cooling: Air
Capacity:

- direct current (DC): 140 A
- in alternating current (AC): 125 A

Duty cycle: 60%.

Tungsten electrode: Ø 0.5 - 2.4 mm



CONFIGURATIONS

	l (m)	Ref
		V
Ø 10/25	4 m	044425
Ø 35/50	4 m	044401



INCLUDED

All the essential consumables for your torch
TIG SR17 in a box:



- 2 nozzles (N5 and N7)
- 2 collar supports (Ø1.6 + Ø2/2.4)
- 2 vice pliers (Ø1.6 + Ø2.4)
- 2 caps (1 short + 1 long)
- 2 tungsten electrodes WR2 AC/DC (Ø1.6 + Ø2.4)

• Also available for sale without the torch (ref. 044678)

CONSUMABLES

STANDARD	Nozzle	Collar support	Standard insulating ring	Collet	head cover																																																							
	<table border="1"> <tr><td>N 4 - Ø 6.5</td><td>(x3)</td><td>038394</td></tr> <tr><td>N 5 - Ø 8.0</td><td>(x3)</td><td>045026</td></tr> <tr><td>N 6 - Ø 9.5</td><td>(x3)</td><td>038400</td></tr> <tr><td>N 7 - Ø 11</td><td>(x3)</td><td>045033</td></tr> <tr><td>N 8 - Ø 12.5</td><td>(x3)</td><td>045286</td></tr> <tr><td>N 10 - Ø 16</td><td>(x3)</td><td>045293</td></tr> <tr><td>N 12 - Ø 19</td><td>(x3)</td><td>045309</td></tr> </table>	N 4 - Ø 6.5	(x3)	038394	N 5 - Ø 8.0	(x3)	045026	N 6 - Ø 9.5	(x3)	038400	N 7 - Ø 11	(x3)	045033	N 8 - Ø 12.5	(x3)	045286	N 10 - Ø 16	(x3)	045293	N 12 - Ø 19	(x3)	045309	<table border="1"> <tr><td>Ø 1.6</td><td>(x3)</td><td>044968</td></tr> <tr><td>Ø 2.0/2.4</td><td>(x3)</td><td>044975</td></tr> <tr><td>Ø 3.2</td><td>(x3)</td><td>045118</td></tr> <tr><td>Ø 4</td><td>(x3)</td><td>047648</td></tr> </table>	Ø 1.6	(x3)	044968	Ø 2.0/2.4	(x3)	044975	Ø 3.2	(x3)	045118	Ø 4	(x3)	047648	<table border="1"> <tr><td>(x1)</td><td>045040</td></tr> </table>	(x1)	045040	<table border="1"> <tr><td>Ø 1.6</td><td>(x3)</td><td>044982</td></tr> <tr><td>Ø 2.0</td><td>(x3)</td><td>044999</td></tr> <tr><td>Ø 2.4</td><td>(x3)</td><td>045019</td></tr> <tr><td>Ø 3.2</td><td>(x3)</td><td>045125</td></tr> <tr><td>Ø 4</td><td>(x3)</td><td>047655</td></tr> </table>	Ø 1.6	(x3)	044982	Ø 2.0	(x3)	044999	Ø 2.4	(x3)	045019	Ø 3.2	(x3)	045125	Ø 4	(x3)	047655	<table border="1"> <tr><td>Short</td><td>(x1)</td><td>044944</td></tr> <tr><td>Long</td><td>(x1)</td><td>044951</td></tr> </table>	Short	(x1)	044944	Long	(x1)
N 4 - Ø 6.5	(x3)	038394																																																										
N 5 - Ø 8.0	(x3)	045026																																																										
N 6 - Ø 9.5	(x3)	038400																																																										
N 7 - Ø 11	(x3)	045033																																																										
N 8 - Ø 12.5	(x3)	045286																																																										
N 10 - Ø 16	(x3)	045293																																																										
N 12 - Ø 19	(x3)	045309																																																										
Ø 1.6	(x3)	044968																																																										
Ø 2.0/2.4	(x3)	044975																																																										
Ø 3.2	(x3)	045118																																																										
Ø 4	(x3)	047648																																																										
(x1)	045040																																																											
Ø 1.6	(x3)	044982																																																										
Ø 2.0	(x3)	044999																																																										
Ø 2.4	(x3)	045019																																																										
Ø 3.2	(x3)	045125																																																										
Ø 4	(x3)	047655																																																										
Short	(x1)	044944																																																										
Long	(x1)	044951																																																										

PRO MOUNTING	Diffuser nozzle	Support for diffuser collar	Insulating ring diffuser	Standard insulating ring	Collet	head cover																														
	<table border="1"> <tr><td>N5 - Ø 8.0</td><td>(x3)</td><td>045071</td></tr> <tr><td>N7 - Ø 11</td><td>(x3)</td><td>045088</td></tr> </table>	N5 - Ø 8.0	(x3)	045071	N7 - Ø 11	(x3)	045088	<table border="1"> <tr><td>Ø 1.6</td><td>(x2)</td><td>045057</td></tr> <tr><td>Ø 2.0/2.4</td><td>(x2)</td><td>045064</td></tr> </table>	Ø 1.6	(x2)	045057	Ø 2.0/2.4	(x2)	045064	<table border="1"> <tr><td>(x1)</td><td>045095</td></tr> </table>	(x1)	045095	<table border="1"> <tr><td>(x1)</td><td>045040</td></tr> </table>	(x1)	045040	<table border="1"> <tr><td>Ø 1.6</td><td>(x3)</td><td>044982</td></tr> <tr><td>Ø 2.0</td><td>(x3)</td><td>044999</td></tr> <tr><td>Ø 2.4</td><td>(x3)</td><td>045019</td></tr> </table>	Ø 1.6	(x3)	044982	Ø 2.0	(x3)	044999	Ø 2.4	(x3)	045019	<table border="1"> <tr><td>Short</td><td>(x1)</td><td>044944</td></tr> <tr><td>Long</td><td>(x1)</td><td>044951</td></tr> </table>	Short	(x1)	044944	Long	(x1)
N5 - Ø 8.0	(x3)	045071																																		
N7 - Ø 11	(x3)	045088																																		
Ø 1.6	(x2)	045057																																		
Ø 2.0/2.4	(x2)	045064																																		
(x1)	045095																																			
(x1)	045040																																			
Ø 1.6	(x3)	044982																																		
Ø 2.0	(x3)	044999																																		
Ø 2.4	(x3)	045019																																		
Short	(x1)	044944																																		
Long	(x1)	044951																																		

RECOMMENDATIONS

	GYSMI E160	GYSMI E200 FV	PROGYS 200A PFC	PROGYS 200E FV CEL	PROGYS 250 TRI	PROGYS CEL 250 TRI	PROGYS FLEX 250 CEL	EXAGON
SR17 V 10/25 connection *	✓	✓	✓	-	-	-	-	-
SR17 V connection 35/50	-	-	-	✓	✓	✓	✓	✓

* Compatible with GYSMI 130P, GYSMI 160P, GYSMI 200P and PROGYS 180A.