

AC Fillee PG EVO Single-Phase

Fillee is a movable storage system battery based. It is designed for professional applications, delivering energy the go, wherever it's needed. Compact, durable, powerful, and adaptable. Fillee sets a new benchmark for mobile energy solutions, empowering businesses to operate efficiently without limits.



| Tech Specs | AC Fillee PG EVO 1P |
|----------------------------|-----------------------|
| Discharging | |
| Continuous Power [kW] | 7,4 |
| Peak Power [kW] | 10 |
| Capacity [kWh] | 22 |
| Discharge Time [h] | 3 (100% load) |
| Discharge Time [h] | 6 (50% load) |
| Batt. Nom. Voltage [V] | 44,4 |
| Output Voltage [V] | 230 (AC) 50 Hz |
| Frequency [Hz] | 50 |
| Output Current [A] | 1P 32A |
| Output socket | CEE 1P+N+PE (32A) |
| Charging | |
| Input socket | CEE 1P+N+PE (16-32 A) |
| Charger Type | Embedded |
| Recharge Power [kW] | 3,5-7 |
| Recharge Time [h] | 3,142857143 |
| Connections | |
| Connectivity | LTE-MQTT |
| Control Panel | LED + Connected App |
| General Information | |
| Battery Type | Li-Ion NMC |
| Dimensions [mm] | 1040 x 610 x 400 mm |
| Weight[kg] | 115 |
| Temperature [°C] | -10+40 |
| IP Protection | IP31 |
| Guaranteed cycles (>80%) | 1500 |