



**Portable Petrol Engine Driven Single-Phase Generator
Output Power 3 kVA single-phase**

Standard Features

- Low oil level cut out device
- 2 x 230 V - 50 Hz Single-phase Schuko outlets protected by circuit breaker
- 1 x 12V DC battery charger outlet protected by fuse

Factory Options

Not available

Accessories On Request

Not available

AC GENERATOR - 50 Hz

Type	synchronous
Single-Phase Power (stand by)	3 kVA - 230 V
Battery Charger	120 W - 12 V - 10 A - CC
Power Factor	0,8
Insulation Class	H
Mechanical Protection	IP 23

NOISE LEVEL

LWA 95	(70 dB at 7m)
Homologated in accordance with the "Directive 2000/14/CE"	

PETROL ENGINE - 3000 RPM

Type	Honda GX 160 OHV - 1 cyl. - 5,5 HP (4 kWm) - 163 cm ³
Fuel	petrol
Cooling system	air
Starting system	manual recoil
Fuel tank capacity	3,6 l
Fuel consumption @ 75%	1,3 l/h

DIMENSIONS AND WEIGHT

L x W x H	585 x 360 x 410 mm
Net Weight	42 kg

SPECIFICATIONS AND PICTURES INTRODUCED HERE ARE SUBJECT TO CHANGE WITHOUT PRIOR NOTICE