



**Portable Petrol Engine Driven Single-Phase Generator
Output Power 5 kVA single-phase**

Standard Features

Low oil level cut out device
2 x 230 V - 50 Hz Single-phase Schuko outlets protected by circuit breaker
1 x 12V DC battery charger outlet protected by fuse

Factory Options

Not available

Accessori a Richiesta

Not available

AC GENERATOR - 50 Hz

Type	synchronous
Single-Phase Power (stand by)	5 kVA - 230 V
Battery Charger	120 W - 12 V - 10 A - CC
Power Factor	0,8
Insulation Class	H
Mechanical Protection	IP 23

NOISE LEVEL

LWA 95 (70 dB at 7m)

PETROL ENGINE - 3000 RPM

Type	Honda GX 270 OHV - 1 cil. - 9 CV (6,6 kWm) - 270 cm ³
Fuel	petrol
Cooling system	air
Starting system	manual recoil
Fuel tank capacity	6 l
Fuel consumption @ 75%	2,2 l/h

DIMENSIONS AND WEIGHT

L x W x H	720 x 480 x 515 mm
Net Weight	63 kg

SPECIFICATIONS AND PICTURES INTRODUCED HERE ARE SUBJECT TO CHANGE WITHOUT PRIOR NOTICE