

EA 5/3 GH

PORTABLE THREE-PHASE POWER GENERATOR / OUTPUT POWER
5,5 KVA THREE-PHASE AND **2 KVA** SINGLE-PHASE /
PETROL ENGINE **3000 GIRI/MIN**

Gen Set Features	+ Low oil level cut out device + 1 x 16 A, 400 V - 50 Hz three-phase EEC socket protected by circuit breaker + 1 x 16 A, 230 V - 50 Hz single-phase EEC socket protected by circuit breaker + Earth Leakage Circuit Breaker (ELCB)	
Gen Set Options (available as factory options)	+ Versions with different voltages + 60 Hz version	
Accessories on Request	+ Trolley	two-wheels and handles
Noise Level	+ LWA 95	(70 dB a 7m)
AC Generator 50 Hz	+ Type	synchronous
	+ Three-phase p. (max.)	5,5 kVA - 400 V
	+ Single-phase p. (max.)	2 kVA - 230 V
	+ Power Factor	0,8
Petrol Engine 3000 rpm	+ Type Honda GX 270 OHV - 1 cil. 9 CV (6,6 kWm) - 270 cm ³ + Fuel petrol + Cooling system air + Starting system manual recoil + Fuel tank capacity 6 l + Fuel consumption @ 75% 2,2 l/h	
Other features	+ Insulation Class	H
	+ Ambient temperature	40 °C
	+ Altitude	1000 mt
	+ Mechanical Protection	IP 23
	+ Dimensions (L x W x H)	730 x 480 x 520 mm
	+ Dry weight	80 kg

EA 5/3 GH



mase
GENERATORS