

GenSet



PTO 63



GEN SET S.p.a.

Via Stazione,5 - 27030 Villanova D' Ardenghi (Pavia) Italy
Tel. (+39) 0382-5091 - Fax (+39) 0382-509-244
E-mail: genset@genset.it - internet: [//www.genset.it](http://www.genset.it)

PTO 63

POWER GENERATOR / OUTPUT POWER 69,3 KVA THREE-PHASE AND 23 KVA SINGLE-PHASE

Gen Set Features	<ul style="list-style-type: none"> + 3 points baseframe + Earth leakage Circuit Breaker + 4 poles main Circuit Breaker + 1 pole Circuit Breaker + Three phase 400 V 125 A EEC socket + Single phase 230 V 32 A EEC socket + Voltmeter + Ammeter + Frequencymeter + Remote control with Frequencymeter (cable 5 m)
AC Generator 50 Hz	<ul style="list-style-type: none"> + Alternator type: 4 poles synchronous brushless - Linz PRO22SB/4 + Alternator voltage regulator: Electronic + Three-phase power (stand-by): 69,3 kVA - 400 V + Three-phase power (prime): 63 kVA - 400 V + Single-phase power: 23 kVA - 230 V + Power factor: $\cos \varphi$ 0,8
Other Features	<ul style="list-style-type: none"> + Insulation Class: H + Ambient temperature: 40 °C + Altitude: 1000 m + Mechanical Protection: IP 23 + Alternator: 1500 rpm + Power take off: 440 rpm + Gear box ratio: 1 : 3,5 + Dimensions (L x W x H): 1435 x 945 x 809 mm + Estimated Weight: 460 kg

At least 2 tractor horsepower (Hp) is required for each kilowatt (kW) of generator output.

Generator set in designed to operate in ambient temperature up to 40 °C and 1000 mt altitude - For higher values of temperature and altitude please consult factory to check available power.