

SERIE LM

LUX M11

LIGHTING TOWER



VERTICAL TELESCOPIC MAST
8.5 m MAX EIGHT



4x300 W MULTI LED LAMPS
4500 m² ILLUMINATED AREA



KUBOTA Z482, 2 CYL. ENGINE
1500 RPM LIQUID COOLED



FUEL CONSUMPTION 0.55 l/h
145 hs. RUNNING TIME



GALVANIZED METAL BODY
80 µm POWDER COATING



RATED OUTPUT: 3.5kVA - 230V
OUTLET SOCKET: 2kVA - 230V



350° MAST ROTATION
ADJUSTABLE FLOODLIGHT



LUXTOWER 
www.luxtower.com

ROUGH DIMENSIONS & WEIGHT

Dimensions min.	mm	2390 X 1380 X 2600
Dimensions max.	mm	2390 X 2370 X 8500
Total weight without fuel	Kg	690

FEATURES

Rotation		350°
Floodlight	W	4 X 300
Lamps		LED
Options		Sun switch light sensor

ALTERNATOR

Model		Linz or Mecc-alte
Frequency	Hz	50 - 60
Noise Level	db at 7 meters	65
Wind stability	Km/h	110
Rated output	kVA/V	3.5 - 230
Auxiliary outlets	kVA	2

ENGINE

Model		Kubota Z482
Fuel		Diesel
r.p.m.		1500
Tank capacity	L	80
Running time	h	145
Fuel consumption	l/h	0.55

 **5 LUX MIN.**

ILLUMINATED AREA

4500 m²

- 5 m range
- 10 m range
- 20 m range
- 30 m range



40'' HC container



16 units

11 units per truck

