




16 240

LUMENS



# LUMAPHORE® LED 200L – 230V

## PRIMO



**LUMAPHORE® 200L complements perfectly the existing LUMAPHORE® LED range. Almost as powerful as the LUMAPHORE® CFL 440, it is lighter, smaller and more durable product. It is fitted with a carrying handle as standard and can be suspended anywhere.**

**LUMAPHORE® 200 L offers powerful illumination of 16000 Lumens with 170 Watts. It is the ideal solution for many industry sectors :**

- Civil engineering
- Rail works
- Road safety departments
- Road surfacing companies
- Water and utilities companies
- Council services
- ...

### Benefits:

- 900 m<sup>2</sup> area of lighting with 170 W output
- 100% immédiate Lighting
- Lightweight
- Carrying handle
- Resistant to adverse weather conditions





# LUMAPHORE® LED 200L – Technical Data

## Electrical Specifications

No. Of LED modules	10
No. Of LEDs per module	42
Total Lighting Output	160 W
Power of electricity supply	170 W
Connecting cable 3x1.5 <sup>2</sup> head	10 m
Average life of LEDs	50000 hrs
Immediate illumination	yes

## Safety Specifications


Protection index	<b>IP44</b>
Wind resistance	NC
Mast with guy wires	Yes
Temperature range for use	-15°/+40°

## Photometric Specifications

Area of illumination	900 m <sup>2</sup>
Colour temperature	4700 °K
Lumens/module	1600
total Lumens	16000
Color rendering index	> 82

## Mechanical Specifications

Diameter	22,5 cm
Length	62 cm
Weight	4,7 Kg
Optimal height for use	3 m
Average assembly time	2 mn



Honda Generator EU10i – 1000 W



Flight case



Carrying handle

## Accessories Available

Telescopic mast with or without winch
Support with 15° angle
1000 W Generator
PMMA Coloured tubes

