



FORCE 165 230V ACX PLASTIC CARRY CASE



Overview

FORCE 165 230V ACX PLASTIC CARRY CASE

cod. 815857

MMA inverter, electrode welding machine in direct current (DC).

Usable electrodes: rutile, basic, stainless steel, cast iron, etc.

Features:

- Reduced weight and dimensions
- High welding current stability in spite of mains voltage fluctuations
- Arc force, hot start and anti-stick devices
- Thermostatic, overvoltage, undervoltage, overcurrent, motorgenerator ($\pm 15\%$) protections.

Complete with MMA welding accessories and plastic carry case.

Technical data

CODE	CODE 815857	A_{MAX}	MAX ABSORBED CURRENT 31 A	IP	PROTECTION DEGREE IP21
V_{1PH}	SINGLE PHASE MAINS VOLTAGE 230 V	P_{MAX}	MAX ABSORBED POWER 4,1 kW	W^H_L	DIMENSIONS 38 - 42 - 17 cm
F	MAINS FREQUENCY 50 / 60 Hz	P_{GEN}	MOTORGENERATOR MINIMUM POWER 6 kW	kg	WEIGHT 5,5 kg
A_{MIN/MAX}	CURRENT RANGE 10 - 150 A	FUSE	MAINS FUSE 16 A	BAR CODE	EAN CODE 800489778955 2
η	%USE (20°C USE) 60% - 150A	η	EFFICIENCY 82 %	PALLETS	PIECES/PALLET 36 pz/pallet
A_{MAX 40°C}	MAX CURRENT 140 A - 7%	φ	POWER FACTOR (cosphi) 0,6	PALLETS	PIECES/PALLET - B 30 pz/pallet - B
V₀	MAX NO LOAD VOLTAGE 72 V	φ_{DC MIN/MAX}	D. USABLE ELECTRODES IN DC 1,6 - 4 mm		



FORCE 165 230V ACX PLASTIC CARRY CASE

(*)%USE:DATUM CREATED BY TELWIN,

Included Accessories



MASK - 712250



COLORADO 150B WORK CLAMP 150A - 712001



DALLAS 300 ELECTRODE HOLDER 300A - 712260



SLAG REMOVER - 712139



FILTER 51X108 - 712257