



## SUPERMIG 380 230-400V



### Overview

#### SUPERMIG 380 230-400V

cod. 822043

MIG-MAG/FLUX/BRAZING welding machine with 4 rolls, separate wire feeder, fit for use in the industrial field. Flexibility of use with a wide range of materials such as steel, stainless steel and aluminium.

Features:

- Very strong
- Numerous steps for regulation of arc voltage
- Regulation of spot welding time
- Two positions for reactance
- Thermostatic protection

Thanks to the extensions (optional) it is possible to increase the working range between wire feeder and powersource up to 10 meters.

Complete with MIG-MAG welding accessories.

### Technical data

<b>CODE</b>	CODE 822043	<b>P<sub>MAX</sub></b>	MAX ABSORBED POWER 15 kW	<b>FX</b>	FLUX CORED WELDING WIRE DIAM. 1 - 1,6 mm
<b>V<sub>3PH</sub></b>	THREE PHASE MAINS VOLTAGE 230 / 400 V	<b>P<sub>60%</sub></b>	ABSORBED POWER AT 60% 8,5 kW	<b>BZ</b>	BRAZING WIRE DIAM. 0,8 - 1,2 mm
<b>F</b>	MAINS FREQUENCY 50 / 60 Hz	<b>φ</b>	POWER FACTOR (cosphi) 0,9	<b>IP</b>	PROTECTION DEGREE IP22
<b>A<sub>MIN</sub> / A<sub>MAX</sub></b>	CURRENT RANGE 40 - 350 A	<b>☀</b>	ADJUSTMENT POSITIONS 18	<b>W<sub>H</sub> / L</b>	DIMENSIONS 89 - 45,3 - 128,5 cm



## SUPERMIG 380 230-400V



MAX CURRENT 350 A - 35 %



STEEL WELDING WIRE DIAMETER 0,6 - 1,6 mm



WEIGHT 101 kg



CURRENT AT 60% 260 A



INOX WELDING WIRE DIAMETER 0,8 - 1,6 mm



EAN CODE 800489779075 6



MAX NO LOAD VOLTAGE 43 V



ALUMINIUM WELDING WIRE DIAM. 0,8 - 1,2 mm

### Included Accessories



ARGON GAS BOTTLE IT ADAPTOR - 432036



GAS REGULATOR 2 MANOMETERS - 722346



CABLE 35 MMQ 3 M WORK CLAMP DX50 - 723030



MT36 MIG TORCH 3 M - 742186