

MG I2000 I-H/AE



Front Panel



GX630 Honda Engine



Lifting Tubular



Stage V

We offer now what others will do tomorrow.



GenSet s.p.a.

Via Stazione 5 - 27030
Villanova d'Ardenghi (PV) - Italy
Phone: +39-0382-5091

commerciale@genset.it
www.genset.it

 **GenSet**
Next Gen technology
for top business.

PORTABLE POWER GENERATOR
OUTPUT POWER 11 kVA SINGLE-PHASE
PETROL ENGINE 3000 RPM
FUEL TANK 29 LT

Standard Features	<ul style="list-style-type: none"> • Low oil level shutdown device • 12V battery • 1 x 16 A, 230V - 50 Hz single-phase EEC socket • 1 x 32 A, 230V - 50 Hz single-phase EEC socket • Protections for power outputs • Earth leakage circuit breaker (ELCB) • Voltmeter • Hourmeter • Central lifting eye
Options available as factory options	<ul style="list-style-type: none"> • Versions with different voltages • 60Hz version • Fitted for AMF-ATS or Remote control operation
Accessories on request	<ul style="list-style-type: none"> • AMF/ATS panel for auto start operation • Remote control
Noise level	<ul style="list-style-type: none"> • Lwa 98 (73 dB a 7 mt)
AC generator - 50Hz	<ul style="list-style-type: none"> • Type: synchronous • Single-phase power (standby): 11 kVA - 230V • Single-phase power (prime): 10 kVA - 230V • Power Factor: $\cos \phi$ 0,8
Petrol Engine 3000 rpm	<ul style="list-style-type: none"> • Type: Honda GX630 - 2 cyl. - STAGE V - 19,8 hp (14,6 kWm) 688 cm³ • Cooling system: air • Starting system: recoil • Fuel tank capacity: 29 lt • Fuel consumption @ 75%: 5,5 lt/h
Other features	<ul style="list-style-type: none"> • Insulation Class: H • Ambient temperature: 40 °C (*) • Altitude: 1000 mt (*) • Mechanical Protection: IP 23 • Dimensions (L x W x H): 904 x 507 x 823 mm • Dry weight: 148 kg

(*) - For altitude and temperature values higher than those listed above, please consult the manufacturer to verify the available power.
In line with our continued development, innovation and voice of customer program, we reserve the right to change data without notice.