

MG 5000 S-Y



Control panel



Central lifting eye



10,5 lt Fuel Tank



Stage V

We offer now what others will do tomorrow.



GenSet s.p.a.

Via Stazione 5 - 27030
Villanova d'Ardenghi (PV) - Italy
Phone: +39-0382-5091

commerciale@genset.it
www.genset.it

GenSet
Next Gen technology
for top business.

SILENCED POWER GENERATOR
OUTPUT POWER 4,25 KVA SINGLE-PHASE
DIESEL ENGINE 3000 RPM
FUEL TANK 10,5 LT

Standard Features	<ul style="list-style-type: none"> • Voltmeter • Hourmeter • Earth leakage circuit breaker • Emergency stop button • Starter battery • 1 x 32 A, 230V - 50 Hz EEC single-phase socket • 1 x 16A, 230V - 50 Hz EEC single-phase socket • Power output protection • Fitted for AMF/ATS or Remote control operation • Central lifting eye
Options available as factory options	<ul style="list-style-type: none"> • Versions with different voltages • 60Hz version • Oversized fuel tank • Automatic voltage regulator (AVR)
Accessories on request	<ul style="list-style-type: none"> • AMF/ATS panel for auto start operation • Trolley: two-wheels and handles • Remote START/STOP kit
Noise level	<ul style="list-style-type: none"> • Lwa 96 (71 dB a 7 mt)
AC generator - 50Hz	<ul style="list-style-type: none"> • Type: synchronous • Single-phase power (max.): 4,25 kVA - 230V • Power Factor: $\cos \phi$ 0,8
Diesel Engine 3000 rpm	<ul style="list-style-type: none"> • Type: Yanmar L70V - 1 cyl. - 6 hp (4,5 kWm) - 320 cm³ • Cooling system: air • Starting system: electric • Fuel tank capacity: 10,5 lt • Fuel consumption @ 75%: 1 lt/h
Other features	<ul style="list-style-type: none"> • Insulation Class: H • Ambient temperature: 40 °C (*) • Altitude: 1000 mt (*) • Mechanical Protection: IP 23 • Dimensions (L x W x H): 815 x 560 x 730 mm • Dry weight: 125 kg

(*) - For altitude and temperature values higher than those listed above, please consult the manufacturer to verify the available power.
 In line with our continued development, innovation and voice of customer program, we reserve the right to change data without notice.