

MG 600 I SS-Y



Control Panel



Movable base



Lifting eye



Stage V

We offer now what others will do tomorrow.



Genset s.p.a.

Via Stazione 5 - 27030
Villanova d'Ardenghi (PV) - Italy
Phone: +39-0382-5091

commerciale@genset.it
www.genset.it

 **GenSet**
Next Gen technology
for top business.

**SUPER SILENCED POWER GENERATOR
OUTPUT POWER 6 kVA SINGLE-PHASE
DIESEL ENGINE 3000 RPM STAGE V
30 Lt FUEL TANK**

<p>Standard Features</p>	<ul style="list-style-type: none"> • 12V built-in battery • 1 x 230V - 32A single-phase EEC socket • 1 x 230V - 16A single-phase EEC socket • 1 x 110V - 32A single-phase EEC socket • 1 x 110V - 16A single-phase EEC socket • Switch breaker • Earth leakage circuit breaker • Emergency stop button • Fuel level gauge • Hourmeter • Central lifting eye • Foreseen for AMF-ATS or Remote control operation • Auto engine protection shutdown system with warning lights for: <ul style="list-style-type: none"> - battery charger failure - low fuel level - low oil pressure
<p>Options available as factory options</p>	<ul style="list-style-type: none"> • Versions with different voltages • 60Hz version
<p>Accessories on request</p>	<ul style="list-style-type: none"> • Remote control unit with 20mt cable • AMF/ATS panel • Trolley: two-wheels and handles
<p>Noise level</p>	<ul style="list-style-type: none"> • Lwa 92 (67 dB a 7 mt)
<p>AC generator - 50Hz</p>	<ul style="list-style-type: none"> • Type: synchronous • Single-phase power (max.): 6 kVA - 230 / 110V • Single-phase power (prime): 5,4 kVA - 230 / 110V • Fattore di potenza: $\cos \phi$ 0,8
<p>Diesel Engine 3600 rpm</p>	<ul style="list-style-type: none"> • Type: Yanmar L100V - STAGEV - 1 cyl. - 435 cm³ • Max power: 8,4 HP (6,3 kWm) • Starting system: electric (12Vdc) • Cooling system: aria • Fuel tank capacity: 30 lt • Fuel consumption @ 75%: 1,5 lt/h
<p>Other features</p>	<ul style="list-style-type: none"> • Insulation Class: H • Ambient temperature: 40 °C (*) • Altitude: 1000 mt (*) • Mechanical Protection: IP 23 • Dimensions (L x W x H): 1160 x 631 x 872 mm • Dry weight: 200 kg

(*) - For altitude and temperature values higher than those listed above, please consult the manufacturer to verify the available power.
In line with our continued development, innovation and voice of customer program, we reserve the right to change data without notice.