

MG 23 I-SY



Front Panel



40 Lt fuel tank



1500 rpm Yanmar engine



Stage V

We offer now what others will do tomorrow.



Genset s.p.a.

Via Stazione 5 - 27030
Villanova d'Ardenghi (PV) - Italy
Phone: +39-0382-5091

commerciale@genset.it
www.genset.it

 **GenSet**
Next Gen technology
for top business.

SILENCED POWER GENERATOR

OUTPUT POWER 20 KVA THREE-PHASE AND 6,6 KVA SINGLE-PHASE

DIESEL ENGINE 1500 RPM

FUEL TANK 40 LT

<p>Standard Features</p>	<ul style="list-style-type: none"> • Auto engine protection shutdown system with warning lights in case of: <ul style="list-style-type: none"> - battery charger failure - low fuel level - low oil pressure - high water temperature • 1 x 32A, 400V three-phase EEC socket • 1 x 32A, 230V single-phase EEC socket • 12V battery • Hourmeter • Voltmeter • Emergency stop button • Fuel level visual indicator • Foreseen for AMF/ATS or Remote control operation • Earth leakage circuit breaker • Thermal protection • Engine oil drain pipe • Central lifting eye
<p>Options available as factory options</p>	<ul style="list-style-type: none"> • Versions with different voltages • 60Hz version • Spark arrester muffler • Controller with digital display • Automatic voltage regulator (AVR) • Engine heater • Oversized fuel tank
<p>Accessories on request</p>	<ul style="list-style-type: none"> • AMF/ATS panel • Remote Start/Stop kit with cable (20 mt) • GRT2W: two-wheels site tow undercarriage
<p>Noise level</p>	<ul style="list-style-type: none"> • Lwa 91 (66 dB a 7 mt)
<p>AC generator - 50Hz</p>	<ul style="list-style-type: none"> • Type: synchronous • Three-phase power (stand-by): 20kVA - 400V • Three-phase power (prime): 18kVA - 400V • Single-phase power (max.): 5,6kVA - 230V • Power Factor: $\cos \phi$ 0,8
<p>Diesel Engine 1500 rpm</p>	<ul style="list-style-type: none"> • Type: Yanmar 4TNV88 - STAGEV - 4 cyl. - 2190 cm³ • Max power: 24,5 hp (18 kWm) • Starting system: electric (12Vdc) • Cooling system: water • Fuel consumption @ 75%: 3,5 lt/h
<p>Other features</p>	<ul style="list-style-type: none"> • Insulation Class: H • Ambient temperature: 40°C (*) • Altitude: 1000 m (*) • Mechanical Protection: IP 23 • Fuel tank capacity: 40 lt • Dimensions (L x W x H): 1650 x 700 x 980 mm • Dry weight: 475 kg

(*) - For altitude and temperature values higher than those listed above, please consult the manufacturer to verify the available power.

In line with our continued development, innovation and voice of customer program, we reserve the right to change data without notice.