

GREEN POWER GP88S-P-N SOUNDPROOF



Product price:

13.629,00 € tax excluded

Product description:

The GREEN POWER 1500 rpm generators are designed for versatile use, from construction sites to industry, from agriculture to civil protection.

Robust welded steel frames with built-in tank of variable capacity produced by Green Power, engines and alternators supplied by the most important manufacturers in the sector and cutting-edge control units are the elements to ensure generators of excellent quality.

The hoods are made of steel, which allows them to be used in tropical environments. The Green Power covers guarantee maximum accessibility for maintenance and cleaning operations.

Green Power's strong point is the design and implementation within the company, a feature that helps to reduce the time to market of the product and allows any customization.

You can choose from several versions:

- Silenced group with AVR-Leroy alternator (automatic control pack)
- Silenced group with high AVR-Mecc alternator (automatic control unit)
- Silenced group with AVR-Stamford alternator (automatic control unit)

The image is purely indicative.

Product features:

Phase: Three phase

Maximum power three phase (KW): 70.4

Continuous power three phase (KW): 64

Maximum power three phase (KVA): 88

Continuous power three phase (KVA): 80
Fuel: Diesel
Frequency (Hz): 50
Voltage (V): 230 / 400
Engine: PERKINS 1104A-44TG2, 4 stroke turbo-aftercooler
Emissions Regulations: NON EMISSIONATO
Engine rpm (rpm): 1500
Speed governor: Mechanical
Starting system: Elettrico
Engine capacity (cm³): 4400
Number cylinders: 4
Cylinders' position: In line
Cooling: Water
Alternator: MECC ALTE ECP32-2L/4
Poles: 4
Protection degree: IP23
Fuel tank capacity (L): 100
Consumption (L/h): 14 al 75% del carico
Running time (h): 7.14 h al 75% del carico
Length (mm): 2260
Width (mm): 1000
Height (mm): 1400
Dry weight (Kg): 1315
Silenced: Yes
Super silenced: Yes
ATS Switch device : Optional
Voltage regulator: AVR