

# GREEN POWER GP198S-P-N SOUNDPROOF

Product price:

## 24.662,00 € tax excluded

### **Product description:**

Ì

The GREEN POWER 1500 rpm generators are designed for versatile use, from construction sites to industry, from agriculture to civil protection.

Robust welded steel frames with built-in tank of variable capacity produced by Green Power, engines and alternators supplied by the most important manufacturers in the sector and cutting-edge control units are the elements to ensure generators of excellent quality.

The hoods are made of steel, which allows them to be used in tropical environments. The Green Power covers guarantee maximum accessibility for maintenance and cleaning operations.

Green Power's strong point is the design and implementation within the company, a feature that helps to reduce the time to market of the product and allows any customization.

### You can choose from several versions:

-Silenced group with AVR-Leroy alternator (automatic control pack)

-Silenced group with high AVR-Mecc alternator (automatic control unit)

-Silenced group with AVR-Stamford alternator (automatic control unit)


The image is purely indicative.

#### Product features:

Phase: Three phase Maximum power three phase (KW): 158.4 Continuous power three phase (KW): 144 Maximum power three phase (KVA): 198

PrestaShop

R



Continuous power three phase (KVA): 180 Fuel: Diesel Frequency (Hz): 50 Voltage (V): 230 / 400 Engine: PERKINS 1106A-70TAG3, turbocharged **Emissions Regulations: NON EMISSIONATO** Engine rpm (rpm): 1500 Speed governor: Mechanical Starting system: Elettrico Engine capacity (cm<sup>3</sup>): 7010 Number cylinders: 6 Cylinders' position: In line Cooling: Water Alternator: MECC ALTE ECO38-1S/4 Poles: 4 Protection degree: IP23 Fuel tank capacity (L): 170 Consumption (L/h): 24.7 Lt/h al 75% del carico Running time (h): 5.06 h al 75% del carico Acoustic pressure: 70 dB(A) Length (mm): 3300 Width (mm): 1100 Height (mm): 1770 Dry weight (Kg): 2100 Silenced: Yes Super silenced: Yes ATS Switch device : Optional Voltage regulator: AVR

Ø.