



# GREEN POWER GP385S-P-N SOUNDPROOF

Product price:

**47.141,00 € tax excluded**

## Product description:

The GREEN POWER 1500 rpm generators are designed for versatile use, from construction sites to industry, from agriculture to civil protection.

Robust welded steel frames with built-in tank of variable capacity produced by Green Power, engines and alternators supplied by the most important manufacturers in the sector and cutting-edge control units are the elements to ensure generators of excellent quality.

The hoods are made of steel, which allows them to be used in tropical environments. The Green Power covers guarantee maximum accessibility for maintenance and cleaning operations.

Green Power's strong point is the design and implementation within the company, a feature that helps to reduce the time to market of the product and allows any customization.

## You can choose from several versions:

- Silenced group with AVR-Leroy alternator (automatic control pack)
- Silenced group with high AVR-Mecc alternator (automatic control unit)
- Silenced group with AVR-Stamford alternator (automatic control unit)

The image is purely indicative.

## Product features:

Phase: Three phase

Maximum power three phase (KW): 308

Continuous power three phase (KW): 280

Maximum power three phase (KVA): 385



Continuous power three phase (KVA): 350  
Fuel: Diesel  
Frequency (Hz): 50  
Voltage (V): 230 / 400  
Engine: PERKINS 2206A-E13TAG2  
Emissions Regulations: NON EMISSIONATO  
Engine rpm (rpm): 1500  
Speed governor: Electronic  
Starting system: Elettrico  
Engine capacity (cm<sup>3</sup>): 12500  
Number cylinders: 6  
Cylinders' position: In line  
Cooling: Water  
Alternator: MECC ALTE ECO38-3LN  
Poles: 4  
Protection degree: IP23  
Fuel tank capacity (L): 230  
Consumption (L/h): 54 Lt/h al 75% del carico  
Running time (h): 5.55 h al 75% del carico  
Acoustic pressure: 70 dB(A)  
Length (mm): 3950  
Width (mm): 1300  
Height (mm): 2100  
Dry weight (Kg): 3840  
Silenced: Yes  
Super silenced: Yes  
ATS Switch device : Optional  
Voltage regulator: AVR