

GREEN POWER GP900A-P OPEN



Product price:

85.833,00 € tax excluded

Product description:

GREEN POWER GP900A-P OPEN GENSET

GREEN POWER GP900A-P OPEN is a three-phase genset with a rated of 900 kVA. It is powered by a Perkins 4006-23TAG3A engine. The genset is equipped with a MECC ALTE ECO43-2S alternator with a voltage of 400 V and a frequency of 50 Hz.

GREEN GP900A-P OPEN is designed for use in commercial and industrial applications, such as construction sites, factories and hospitals. It is ideal for providing emergency in the event of a blackout or for powering industrial machinery.

The GREEN POWER GP900A-P OPEN is a robust and reliable product that offers a number of advantages, including:

Versatility: the GREEN POWER GP900A-P genset can be used in a variety of applications.

Reliability: the GREEN POWER GP900A-P genset is robust and durable.

Efficiency: the genset has low consumption.

Safety: GREEN POWER GP900A-P genset is equipped with advanced safety systems.

Technical characteristics GENSET GREEN GP900A-P:

Maximum three-phase: 900 KV

Maximum three-phase: 720 KW

Fuel: Diesel

Voltage: 230/400 V

Engine: Perkins 4006-23TAG3A

Starter: Electric

Length: 4000 mm
Width: 1800 mm
Height: 2350 mm
Weight: 6500 Kg

You can choose from four GREEN GP900A-P OPEN versions:

- Open genset with high AVR-Mecc alternator (manual control unit)
- Open-group with high-speed AVR-Mech alternator (automatic power pack)
- Open group with AVR-Stamford alternator (manual power pack)
- Open genset with AVR-Stamford alternator (automatic power pack)

GREEN GP900A-P OPEN is a robust and reliable product that offers a number of advantages, including:

Versatility: it can be used in a variety of applications.

Reliability: it is robust and durable.

Efficiency: low consumption.

Safety: it is equipped with advanced safety systems.

If you are looking for a similar product GREEN GP900A-P or with similar features click [HERE](#).

Images purely indicative.

Product features:

Phase: Three phase
Maximum power three phase (KW): 396
Continuous power three phase (KW): 480
Maximum power three phase (KVA): 495
Continuous power three phase (KVA): 600
Fuel: Diesel
Frequency (Hz): 50
Voltage (V): 230 / 400
Engine: 1506A-E88TAG2

Engine rpm (rpm): 1500
Speed governor: Electronic
Starting system: Electric
Engine capacity (cm³): 8800
Number cylinders: 6
Cylinders' position: In line
Cooling: Water
Alternator: LINZ PRO 22SD/4 - Sincrono
Poles: 4
Fuel tank capacity (L): 400
Consumption (L/h): 24.7 Lt/h al 75% del carico
Running time (h): 9.62 h al 75% del carico
Length (mm): 4
Width (mm): 1800
Height (mm): 2350
Dry weight (Kg): 3430
Silenced: No
Super silenced: No
ATS Switch device : Optional
Voltage regulator: AVR