



GREEN POWER GP2200A/P OPEN (MANUAL CONTROL UNIT)

Product price:

264.579,00 € tax excluded

Product description:

The GREEN POWER 1500 rpm generators are designed for versatile use, from construction sites to industry, from agriculture to civil protection.

Robust welded steel frames with built-in tank of variable capacity produced by Green Power, engines and alternators supplied by the most important manufacturers in the sector and cutting-edge control units are the elements to ensure generators of excellent quality.

The hoods are made of steel, which allows them to be used in tropical environments. The Green Power covers guarantee maximum accessibility for maintenance and cleaning operations.

Green Power's strong point is the design and implementation within the company, a feature that helps to reduce the time to market of the product and allows any customization.

The image is purely indicative.

Product features:

Phase: Three phase

Maximum power three phase (KW): 396 Continuous power three phase (KW): 480 Maximum power three phase (KVA): 495 Continuous power three phase (KVA): 600

Fuel: Diesel

Frequency (Hz): 50 Voltage (V): 230 / 400 Engine: 1506A-E88TAG2 Engine rpm (rpm): 1500 Speed governor: Electronic





Starting system: Electric Engine capacity (cm³): 8800

Number cylinders: 12 Cylinders' position: In line

Cooling: Water

Alternator: LINZ PRO 22SD/4 - Sincrono

Poles: 4

Fuel tank capacity (L): 520

Consumption (L/h): 24.7 Lt/h al 75% del carico Running time (h): 9.62 h al 75% del carico

Length (mm): 4500 Width (mm): 2220 Height (mm): 2350 Dry weight (Kg): 3430

Silenced: No

Super silenced: No

ATS Switch device: Optional

Voltage regulator: AVR